



101^{Q&As}

Application Delivery Fundamentals

Pass F5 101 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/101.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by F5 Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is the purpose of MAC masquerading?

- A. to prevent ARP cache errors
- B. to minimize ARP entries on routers
- C. to minimize connection loss due to ARP cache refresh delays
- D. to allow both BIG-IP devices to simultaneously use the same MAC address

Correct Answer: C

QUESTION 2

A GTM System would like to ensure that a given LTM System is reachable and iQuery communication is allowed prior to sending it client request. What would be the simplest monitor template to use?

- A. TCP
- B. ICMP
- C. HTTP
- D. BIG-IP
- E. SNMP

Correct Answer: D

QUESTION 3

When is a Virtual Server hosted by an LTM System defined with two IP addresses?

- A. Two addresses are used to define the Virtual Server when it is managed by redundant LTM Systems.
- B. Two addresses are used to define some Virtual Servers so that the GTM System can choose the better address when resolving the name.
- C. Two addresses are used to define Virtual Servers when the LTM System hosting it is behind a firewall that is translating the Virtual Server address.
- D. Two addresses are used to define a Virtual Server when the Wide-IP should resolve to a different address depending on which LTM System is active.

Correct Answer: C



QUESTION 4

How is MAC masquerading configured?

- A. Specify the desired MAC address for each VLAN for which you want this feature enabled.
- B. Specify the desired MAC address for each self-IP address for which you want this feature enabled.
- C. Specify the desired MAC address for each VLAN on the active system and synchronize the systems.
- D. Specify the desired MAC address for each floating self-IP address for which you want this feature enabled.

Correct Answer: A

QUESTION 5

Which of these statements about a stream profile is false?

- A. It is applied to an HTTP class profile.
- B. It is not recommended for telnet traffic.
- C. It can replace one data string for another for all traffic going through a virtual server.
- D. It applies to both inbound and outbound traffic.
- E. It will not inspect HTTP headers when an HTTP profile is present.

Correct Answer: A

[101 PDF Dumps](#)

[101 Practice Test](#)

[101 Braindumps](#)