

132-S-900.7^{Q&As}

Avaya IP Telephony Design Elective Exam

Pass Avaya 132-S-900.7 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/132-s-900-7.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Avaya Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Which two design issues relate to increasing security in VoIP converged solutions? (Choose two.)

- A. suggesting upgrading LAN switches to support QoS
- B. defining VLANs to limit access from specific IP endpoints
- C. considering encryption on IP calls for protection from eavesdropping
- D. considering G.729 compression to protect IP calls from eavesdropping

Correct Answer: BC

QUESTION 2

A customer wants to use an Avaya S87xx Media Server with Avaya G700 Gateways at remote locations. Each G700 Gateway will include an S8300 Local Survivable Processor and approximately 75 IP sets incorporating G.711. What Avaya feature allows IP sets to register with the S8300 if connectivity to the S87xx is lost?

- A. Local CLAN board
- B. Alternate Gatekeeper
- C. S8300 Auto-Registration
- D. Gateway Alternate Redirection

Correct Answer: B

QUESTION 3

Why is Port Usage Rate (PUR) a better measurement than Call Usage Rate (CUR) to evaluate how busy a system is in support of call volume?

- A. Busy ports can be identified, occupied time slots cannot.
- B. Occupied time slots can be identified, busy ports cannot.
- C. PUR uses more precise equations to calculate results than CUR.
- D. PUR is based on Centum Call Seconds (CCS), which are more widely understood.

Correct Answer: A

QUESTION 4

A major call center outsourcer is in the process of implementing a disaster recovery location and is placing an S8500 Media Server configured as an Enterprise Survivable Server (ESS) at their backup facility. To successfully design a



solution that meets the customer needs for survivability and prioritization, what must be done when deploying and administering the ESS servers? (Choose two.)

- A. Avoid overloading the network resources with excessive call traffic
- B. Avoid fragmenting the system so the ESS server controls as much of the network as possible

C. Ensure that the Manual Backup Server is configured in the priority list of each IP Server Interface (IPSI)

D. Ensure that every Local Survivable Processor (LSP) is aware of any G650 Media Gateways that will register to it in the event of a network outage

Correct Answer: AB

QUESTION 5

Which terminology correctly describes the relationship between duplicated SES proxies?

- A. Active and Backup
- B. Active and Standby
- C. Primary and Backup
- D. Primary and Standby
- Correct Answer: C

132-S-900.7 Practice Test

132-S-900.7 Study Guide

132-S-900.7 Exam Questions