



156-115.80^{Q&As}

Check Point Certified Security Master - R80

Pass CheckPoint 156-115.80 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/156-115-80.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CheckPoint Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which IPS command debug tool can you use for troubleshooting IPS traffic?

- A. ips debug traffic -o IPSdebug
- B. ips debug -f /var/log/IPSdebug.txt
- C. debug ips enable -o IPSdebug
- D. ips debug -o IPSdebug

Correct Answer: D

Reference: https://sc1.checkpoint.com/documents/R76/CP_R76_CLI_WebAdmin/84627.htm#o84632

QUESTION 2

Which daemon is used for Geo protection?

- A. in.geod
- B. cphamcset
- C. fwd
- D. cpd

Correct Answer: A

Reference: https://supportcenter.checkpoint.com/supportcenter/portal?eventSubmit_doGoviewsolutiondetails=&solutionid=sk97638

QUESTION 3

Static NAT has been configured and NAT rules were created automatically. The global properties option "Translate destination on client side" is not checked. Clients are complaining that they are not able to connect to one of your web servers using its public address. How would you solve the problem without changing the global properties and reinstalling the security policy?

- A. On the security gateway, add a static route for the web server's public ip address
- B. Rebooting the security gateway will resolve the problem
- C. You will have the global properties and reinstall the security policy
- D. Configure manual NAT

Correct Answer: D

**QUESTION 4**

An organization has 3 sites; 1 Headquarters (HQ) site and 2 remote sites. The remote sites are connected to the HQ through site-to-site VPNs and phone communication is done using standard SIP. There is an issue with VOIP calls where one side cannot hear the other over the phone. As a test, they decide to disable protocol inspection for SIP. How can this be achieved?

- A. Select the existing SIP Service, change the Protocol type to None
- B. Create a new UDP 5060 service, change the protocol type to None
- C. Create a new TCP 5060 service, change the protocol type to None
- D. Select the existing SIP service, change the protocol to None in advance settings.

Correct Answer: D

QUESTION 5

What is the command to check the number of CoreXL firewall instances?

- A. show corexl stat
- B. fw ctl multik stat
- C. coreXL_admin stat
- D. fw ctl corexl stats

Correct Answer: B

[156-115.80 PDF Dumps](#)

[156-115.80 Exam Questions](#)

[156-115.80 Braindumps](#)