



# 1D0-437<sup>Q&As</sup>

CIW PERL FUNDAMENTALS

**Pass CIW 1D0-437 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1d0-437.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by CIW Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Which of the following is a valid subroutine name?

- A. \_funct7
- B. get-pass
- C. #sub1
- D. @passwd

Correct Answer: A

---

### QUESTION 2

Consider the following program code:

```
@arrayA = (10, 20, 30);
```

```
@arrayB = @arrayA;
```

```
$arrayB[1] = 40;
```

```
print $arrayA[1];
```

What is the output of this code?

- A. 10
- B. 20
- C. 30
- D. 40

Correct Answer: B

---

### QUESTION 3

Consider the program code in the attached exhibit.



```
$string = "BOBBY";  
$string =~ s/^[BO][^O][^O]/ROBERT/;  
$string =~ s/^\w{2,}B(.*)/G$1RUDE/;  
$string =~ s/^[R|B]O(.*)/$1/;  
$string =~ s/^\....$/JOHN/;  
print $string;
```

What is the result of executing this program code?

- A. The code will output the following: BOBBY
- B. The code will output the following: GERTRUDE
- C. The code will output the following: JOHN
- D. The code will output the following: ROBERT

Correct Answer: B

#### QUESTION 4

Consider the program code in the attached exhibit.

```
print (multiply(5, 10));  
  
sub multiply  
{  
    $_[1] * $_[2];  
}
```

What is the result of executing this program code?

- A. The code will output the following: 50
- B. The code will output the following: 0
- C. The code will output the following: 5
- D. The code will output the following: multiply(5, 10)

Correct Answer: B

**QUESTION 5**

Which of the following choices demonstrates the correct syntax for creating a hash?

A. `%passwd = ("denise", "robert", "yolanda") => ("pass1", "pass2", "pass3");`

B. `%passwd() = ("denise", "pass1", "robert", "pass2", "yolanda", "pass3");`

C. `%passwd = (denise=> "pass1", robert=> "pass2", yolanda=> "pass3");`

D. `%passwd{3} = ("denise", "robert", "yolanda") => ("pass1", "pass2", "pass3");`

Correct Answer: C

[1D0-437 VCE Dumps](#)

[1D0-437 Practice Test](#)

[1D0-437 Exam Questions](#)