



1Y0-230^{Q&As}

Citrix NetScaler 12 Essentials and Unified Gateway

Pass Citrix 1Y0-230 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1y0-230.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which setting can a Citrix Administrator use to reduce server load, improve response time and increase the number of SSL transactions per second on a SSL virtual server created with default settings?

- A. Session Reuse
- B. SSLv3
- C. Session Timeout
- D. SSLv2 Redirect

Correct Answer: C

Reference: <https://docs.citrix.com/en-us/netscaler/12/load-balancing/load-balancing-manage-clienttraffic/client-idle-timeout-value.html>

QUESTION 2

Which NetScaler mode is commonly referred to as 'inline mode'?

- A. One-Arm Mode
- B. Use Source IP (USIP)
- C. MAC-based Forwarding
- D. Two-Arm Mode

Correct Answer: D

Explanation: In an inline mode (also called two-arm mode) setup, you connect the NetScaler appliance to the network through multiple VLANs. Reference: <https://docs.citrix.com/zh-cn/netscaler/11/traffic-management/load-balancing/load-balancinginlinemode.html>

QUESTION 3

Scenario: A Citrix Administrator needs to implement an Citrix ADC solution. The administrator needs the appliance to be able to grow with the increasing demand for bandwidth and performance.

Which Citrix ADC platform with the administrator choose to accommodate the increasing demand for bandwidth and performance?

- A. SDX
- B. VPX
- C. MPX



D. CPX

Correct Answer: C

QUESTION 4

A Citrix Administrator has deployed a new NetScaler MPX appliance in the demilitarized (DMZ) with one interface in the DMZ and the other on the internal network.

In which mode should the administrator deploy the NetScaler?

- A. One-Arm
- B. Two-Arm
- C. Forward Proxy
- D. Transparent

Correct Answer: D

QUESTION 5

Scenario: A Junior Citrix Administrator needs to create a Content Switching virtual server on a NetScaler high availability (HA) pair. The NSIP addresses are 192.168.20.10 and 192.168.20.11. The junior administrator connects to NSIP address 192.168.20.10 and saves the changes. The following day, a Senior Citrix Administrator tries to test the new Content Switching virtual server, but it is NOT working. The senior administrator connects to the HA pair and everything the junior administrator configured is gone. Why did the NetScalers lose the newly added configurations?

- A. The NetScaler appliances are NOT at the same firmware version
- B. The junior administrator connected to the NSIP of the secondary NetScaler in the HA pair
- C. Both NetScalers in the HA pair restarted overnight, losing the configuration
- D. The junior administrator made the changes and did NOT force a failover to save the configuration

Correct Answer: C

[1Y0-230 VCE Dumps](#)

[1Y0-230 Practice Test](#)

[1Y0-230 Exam Questions](#)