



1Y0-241^{Q&As}

Deploy and Manage Citrix ADC with Traffic Management

Pass Citrix 1Y0-241 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1y0-241.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which setting is responsible for reducing the server load, improving response time, and increasing the number of SSL transactions per second on an SSL vServer?

- A. SSLv3
- B. Session timeout
- C. SSLv2 redirect
- D. Session reuse

Correct Answer: D

QUESTION 2

A Citrix Administrator needs to use a client's IP address as the source IP address for Citrix ADC-to-server connections. Which Citrix ADC mode can the administrator use to meet this requirement?

- A. USNIP
- B. Layer 2
- C. Layer 3
- D. USIP

Correct Answer: D

When you enable the USIP address mode of a NetScaler appliance, the appliance forwards each packet to the appropriate back end server with the client IP address. <https://support.citrix.com/article/CTX121974>

QUESTION 3

A Citrix Administrator deploys a new Citrix ADC MPX appliance in the demilitarized zone (DMZ), with one interface in the DMZ and the other on the internal network. In which mode should the administrator deploy the Citrix ADC?

- A. One-arm
- B. Two-arm
- C. Transparent
- D. Forward proxy

Correct Answer: B

QUESTION 4



To improve page-rendering time a Citrix Administrator needs to overcome the connection limitation by enabling client browsers to simultaneously download more resources. What should the administrator enable while configuring the front end optimization (FEO) feature?

- A. HTML comments removal
- B. Image lazy loading
- C. CSS import to link
- D. Domain sharding

Correct Answer: D

QUESTION 5

A Citrix Administrator needs to configure a Citrix ADC high availability (HA) pair with each Citrix ADC in a different subnet. What does the administrator need to do for HA to work in different subnets?

- A. Configure SyncVlan
- B. Turn on fail-safe mode.
- C. Turn on HA monitoring on all interfaces
- D. Turn on Independent Network Configuration (INC) mode.

Correct Answer: D

In Azure Deployments for example you use this. The correct answer is the Independent Network Configuration (INC). <https://docs.citrix.com/en-us/citrix-adc/current-release/deploying-vpx/deploy-vpx-on-azure/configure-ha-pair-with-alb-floating-ip-disabled-mode.htm>

[Latest 1Y0-241 Dumps](#)

[1Y0-241 Practice Test](#)

[1Y0-241 Exam Questions](#)