



1Y0-253^{Q&As}

Implementing Citrix NetScaler 10.5 for App and Desktop Solutions

Pass Citrix 1Y0-253 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1y0-253.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Scenario: A Citrix Administrator has configured two virtual servers (vServer1 and vServer2). The administrator would like to set up the virtual servers so that only when vServer1 is offline, vServer2 will become active.

What should the administrator configure to achieve this goal?

- A. Service group
- B. Spillover method
- C. Backup virtual server
- D. Spillover backup action

Correct Answer: C

QUESTION 2

Various users report that while accessing the Citrix NetScaler Gateway virtual server they get an error message that the public SSL certificate is NOT trusted. Which three steps should a Citrix Administrator take on the NetScaler to resolve this issue? (Choose three.)

- A. Import the root certificate.
- B. Import the intermediate certificate.
- C. Download the root certificate from the vendor.
- D. Link the root certificate to the intermediate certificate.
- E. Download the intermediate certificate from the vendor.
- F. Link the intermediate certificate to the existing server certificate.

Correct Answer: BEF

QUESTION 3

An administrator needs to implement a solution to provide users with remote access to applications from tablet devices using Citrix Receiver.

Which component is required to fulfill these requirements?

- A. Citrix Web Interface
- B. Citrix Single Sign-on



C. Citrix Provisioning Services

D. Citrix Merchandising Server

Correct Answer: D

QUESTION 4

Scenario: A company had a single datacenter location with a single NetScaler installed. A second datacenter location was added and an administrator installed a second Citrix NetScaler at the second datacenter location. The NetScaler is used for load balancing internal infrastructure solutions. The administrator plans to configure the environment so that it will continue to work even if there is a datacenter failure. Only the primary datacenter location is connected to the Internet. The configuration has to be synchronized automatically so that the configuration of both appliances is always identical. How should the administrator configure the NetScaler devices so that continuity is maintained in the event of a datacenter failure?

A. As a GSLB cluster

B. In a vRRP configuration

C. As a high availability pair

D. As standalone appliances

Correct Answer: C

QUESTION 5

Scenario: A NetScaler Gateway is configured to use RADIUS for authentication. A Citrix Administrator

needs to know which NetScaler IP (NSIP) address is used for outgoing RADIUS traffic.

How can the administrator verify which NSIP is used?

A. Check the ns.log file.

B. Use the ping command.

C. Check the messages log file.

D. Use the nstcpdump.sh command.

Correct Answer: D

[Latest 1Y0-253 Dumps](#)

[1Y0-253 VCE Dumps](#)

[1Y0-253 Study Guide](#)