



1Y0-351^{Q&As}

Citrix NetScaler 10.5 Essentials and Networking

Pass Citrix 1Y0-351 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1y0-351.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A network engineer might choose to use SSL_Bridge instead of a SSL virtual server in order to _____. (Choose the correct option to complete the sentence.)

- A. be able to decrypt the SSL traffic
- B. enable use of OCSP for revoked certificates
- C. pass user certificates to the back-end servers
- D. enable SSL server certificates on the service group

Correct Answer: C

QUESTION 2

Which load-balancing method is used in connection mirroring and firewall load balancing?

- A. URL Hash
- B. Source IP Source Port Hash
- C. Destination IP Hash
- D. Call ID Hash

Correct Answer: B

QUESTION 3

When a network engineer logs onto a new NetScaler device in the London datacenter, data output indicates that the device is NOT configured for the local time.

How can the network engineer synchronize the correct time with an NTP server in the local data center?

- A. Configure the correct time from the GUI and restart.
- B. Modify the ntp.conf and rc.netscaler files and restart.
- C. Logon using the nsrecover/nsroot credentials and restart.
- D. Configure the NetScaler as a secondary NTP server and restart.

Correct Answer: B

QUESTION 4

When would it be necessary to configure Failover Interface Set (FIS) in an environment that has two NetScaler



appliances in high availability (HA) mode?

- A. Link redundancy is required.
- B. Route monitors are required.
- C. HA monitor is disabled in some interfaces.
- D. The NetScaler appliances are configured on different networks.

Correct Answer: A

QUESTION 5

A network engineer has noted that the primary node in an HA pair has been alternating as many as three times a day due to intermittent issues.

What should the engineer configure to ensure that HA failures are alerted?

- A. LACP
- B. SNMP
- C. Route monitors
- D. Failover Interface Set

Correct Answer: B

[Latest 1Y0-351 Dumps](#)

[1Y0-351 VCE Dumps](#)

[1Y0-351 Practice Test](#)