



# 1Y0-A21<sup>Q&As</sup>

Basic Administration for Citrix NetScaler 9.2

## Pass Citrix 1Y0-A21 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1y0-a21.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

Scenario: A company has contracts with multiple ISPs and would like to use all of them for Internet connections. The company also plans to use a NetScaler system for load balancing and failover.

What can an administrator configure to ensure that all ISP connections are being used and return traffic maintains the same path as the inbound traffic in this environment?

- A. Round robin load balancing with INAT configured
- B. Link load balancing with RNAT and USNIP enabled
- C. Multiple VLANs with Ingress rules and USIP enabled
- D. A load balancing policy with the appropriate preferred IP and preferred port parameters configured

Correct Answer: B

---

### QUESTION 2

Scenario: An administrator set up a NetScaler in an HA configuration. When the Primary node was rebooted due to a power failure, the failover did NOT occur as expected.

Which configuration settings must have prevented the failover in the above scenario?

- A. Primary node is set to fail-safe mode.
- B. Primary node is set to stay secondary.
- C. Secondary node is set to do not failover.
- D. Secondary node is set to stay secondary.

Correct Answer: D

---

### QUESTION 3

An administrator has configured several virtual servers in a network environment and needs to determine their bandwidth utilization.

Which information from the Dashboard can the administrator leverage to determine the bandwidth utilization for the virtual servers?

- A. Requests vs. responses
- B. Request bytes vs. response bytes
- C. Current client connections vs. current server connections



---

D. Current server connections vs. current client Est connections

Correct Answer: B

---

#### QUESTION 4

Scenario: An administrator needs to configure load balancing for a web farm so that traffic will NOT be dropped when the virtual server is marked down. Route Health Injection (RHI) and GSLB are NOT configured in this environment.

The administrator can configure \_\_\_\_\_ or \_\_\_\_\_ so that it will receive traffic when the virtual server is marked down. (Choose the two options that correctly complete the sentence.)

- A. a redirect URL string
- B. another NetScaler system
- C. the name of a backup virtual server
- D. the node ID of the secondary in the HA pair

Correct Answer: AC

---

#### QUESTION 5

Scenario: An administrator plans to set up a NetScaler in an HA configuration. The two nodes in the HA pair are located on two separate networks.

Which setting must the administrator configure on each node to ensure that both nodes in the HA pair can synchronize configuration and propagate commands?

- A. Add static route for remote node network
- B. Add route monitor for remote node network
- C. Turn on Independent Router Configuration (IRC)
- D. Turn on Independent Network Configuration (INC) mode

Correct Answer: D

[Latest 1Y0-A21 Dumps](#)

[1Y0-A21 Study Guide](#)

[1Y0-A21 Exam Questions](#)