



# 1Z0-067<sup>Q&As</sup>

Upgrade Oracle9i/10g/11g OCA to Oracle Database 12c OCP

**Pass Oracle 1Z0-067 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1z0-067.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Examine the RMAN commands:

```
RMAN> CONNECT TARGET "sbu@prod AS SYSBACKUP"; RMAN> CONNECT AUXILIARY "sbu@dup_db AS  
SYSBACKUP"; RMAN> DUPLICATE TARGET DATABASE TO dup_db FROM ACTIVE DATABASE PASSWORD FILE  
SECTION SIZE 400M;
```

Which statement is true about the DUPLICATE command?

- A. It succeeds and creates multisection backup sets that are used for active database duplication
- B. It fails because there is no connection to a recovery catalog
- C. It succeeds only if the target database is in MOUNT state
- D. It fails because no parallel channels are allocated for the auxiliary database

Correct Answer: A

---

### QUESTION 2

Which three statements are true about compression of backup sets?

- A. Compressed backups can only be written to media.
- B. Binary compression creates performance overhead during a backup operation.
- C. Unused blocks below the high-water mark are not backed up.
- D. Compressed backups cannot have section size defined during a backup operation
- E. It works only for locally managed tablespaces.

Correct Answer: BCE

"RMAN also skips other datafile blocks that do not currently contain data, if all of the following conditions apply: The COMPATIBLE initialization parameter is set to 10.2 There are currently no guaranteed restore points defined for the database The datafile is locally managed The datafile is being backed up to a backup set as part of a full backup or a level 0 incremental backup The backup set is being created on disk. References:  
[https://docs.oracle.com/cd/B19306\\_01/backup.102/b14194/rcmsynta009.htm#i1015382](https://docs.oracle.com/cd/B19306_01/backup.102/b14194/rcmsynta009.htm#i1015382)

---

### QUESTION 3

Your database is running in archive log mode. Examine the parameters for your database instance:

```
LOG_ARCHIVE_DEST_1 =\\LOCATION=/disk1/arch MANDATORY\\ LOG_ARCHIVE_DEST_2  
=\\LOCATION=/disk2/arch\\ LOG_ARCHIVE_DEST_3 =\\LOCATIO=/disk3/arch\\ LOG_ARCHIVE_DEST_4  
=\\LOCATIONs/disk4/arch\\ LOG_ARCHIVE_MIN_SUCCEED_DEST = 2
```

While the database is open, you notice that the destination set by the log\_archive\_dest\_1 parameter is not available. All



redo log groups have been used.

What happens at the next log switch?

- A. The database instance hangs and the redo log files are not overwritten.
- B. The archived redo log files are written to the fast recovery area until the mandatory destination is made available.
- C. The database instance is shutdown immediately.
- D. The destination set by the log\_archive\_dest parameter is ignored and the archived redo log files are created in the next two available locations to guarantee archive log success.

Correct Answer: A

Explanation: Made more logfile switch until all redos groups are full. first log switch succeeds, second also succeeds then next will hang database.

---

#### QUESTION 4

Which two options can be configured for an existing database by using the Database Configuration Assistant (DBCA)?

- A. Database Resident Connection Pooling
- B. Oracle Suggested Backup Strategy
- C. Database Vault in ORACLE\_HOME
- D. Nondefaultblocksize tablespaces
- E. Configure Label Security

Correct Answer: CE

---

#### QUESTION 5

Which two statements are true about service creation for pluggable databases (PDBs)?

- A. When a PDB is created, a service is automatically started in the instance with the same name as the PDB.
- B. The default service that is automatically created by a database at the time of PDB creation can be dropped, provided a new additional service is created.
- C. A database managed by Oracle Restart can have additional services created or existing services modified by using the srvctl utility for each PDB.
- D. Only a common user can create additional services for a PDB.
- E. When a PDB is created, a service with the same name as the PDB is created in the PDB.

Correct Answer: AC

---



VCE & PDF

GeekCert.com

<https://www.geekcert.com/1z0-067.html>

2024 Latest geekcert 1Z0-067 PDF and VCE dumps Download

---

[Latest 1Z0-067 Dumps](#)

[1Z0-067 VCE Dumps](#)

[1Z0-067 Braindumps](#)