



1Z0-400^{Q&As}

Border Controller Implementation Essentials

Pass Oracle 1Z0-400 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1z0-400.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Session Initiation Protocol (SIP) is an Application layer control protocol that performs which two functions?

- A. Establish, modify and terminate multimedia sessions.
- B. Reserve resources for multimedia sessions.
- C. Provide network transport services for real-time applications such as voice and video.
- D. Describe the supported media attributes for the session.
- E. Support redirection services.

Correct Answer: AC

QUESTION 2

The _____ parameter in the sip-interface element indicates how often a User Agent (UA) located behind a NAT should re-register with the Session Border Controller.

- A. nat-interval
- B. nat-traversal
- C. registration-interval
- D. nat-mode
- E. min-reg-expire

Correct Answer: B

QUESTION 3

You are enabling management access on a network interface in the Session Border Controller. Which two are applicable?

- A. add-snmp-ip
- B. snmp-address
- C. add-hip-ip
- D. telnet-port
- E. set-hip

Correct Answer: BD



QUESTION 4

High availability (HA) nodes identify one another by their _____ names.

- A. Identifier
- B. Host
- C. Mib-system-name
- D. Target
- E. Wancom0 name

Correct Answer: D

QUESTION 5

Which statement is TRUE about the phy-interface configuration element?

- A. A phy-interface element must be configured for each interface used for signaling and/or media.
- B. All modifications to the phy-interface configuration element require a reboot of the Net-Net 4500.
- C. Only one phy-interface configuration element is created for all signaling/media interfaces.
- D. The wancom interfaces used for high availability do not require explicit phy-interface configuration elements.
- E. Configuration elements used to carry signaling and/or media must be designated as type "Control".

Correct Answer: B

[1Z0-400 Practice Test](#)

[1Z0-400 Study Guide](#)

[1Z0-400 Braindumps](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

- 100% Guaranteed Success
- 100% Money Back Guarantee
- 365 Days Free Update
- Instant Download After Purchase
- 24x7 Customer Support
- Average 99.9% Success Rate
- More than 800,000 Satisfied Customers Worldwide
- Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.geekcert.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket:



 One Year Free Update <p>Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 Money Back Guarantee <p>To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 Security & Privacy <p>We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.
All trademarks are the property of their respective owners.
Copyright © geekcert, All Rights Reserved.