



# 1Z0-404<sup>Q&As</sup>

Oracle Communications Session Border Controller 7 Basic Implementation Essentials

**Pass Oracle 1Z0-404 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1z0-404.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

To ensure proper operation of a Session Border Controller HighAvailability (HA) pair, it is critical that both of the devices can originate legitimate traffic on media interfaces independent of the network interface IP address.

How is this type of traffic accommodated?

- A. by setting the pri-utility-addr, sec-utility-addr, and sec-gateway values to addresses in the same subnet as the IP address configured on the management interfaces
- B. by setting the pri-utility-addr, sec-utility-addr, and sec-gateway values to addresses in the same subnet as the IP address configured on the media interfaces
- C. by setting the utility address and sec-gateway values to addresses in different subnets as the IP address configured on the wancom interfaces
- D. by setting a unique address on the wancom1 and wancom2 interfaces via the utilityaddress command
- E. via the utility address parameters on the wancom1 and wancom2 interfaces

Correct Answer: A

---

### QUESTION 2

Which three options are valid ways to apply Header Manipulation Rules (HMRs) to your existing configuration?

- A. Navigate to the network-interface configuration element and configure the in-manipulationid parameter.
- B. Navigate to the session-agent configuration element and configure the in-manipulationid parameter.
- C. Navigate to the sip-interface configuration element and configure the in-manipulationid parameter.
- D. Navigate to the session-agent configuration element and configure the in-manipulationid parameter.
- E. Navigate to the session-group configuration element and configure the in-manipulationid parameter.

Correct Answer: ABC

---

### QUESTION 3

You are configuring access rules in a Session Border Controller Peering architecture.

Which two configuration steps are required to allow access only from User Agents (UAs) in a specific IP subnet? (Choose two.)

- A. Navigate to the sip-port configuration element and set the allow-anonymous parameter to realm-prefix.
- B. Navigate to the session-agent configuration element and set the ip-address parameter to the IP address of your trusted User Agent (UA).
- C. Navigate to the sip-port configuration element and set the allow-anonymous parameter to agents-only.



- D. Navigate to the sip-port configuration element and set the allow-anonymous parameter to all.
- E. Navigate to therealm-config configuration element and set the addr-prefix parameter to the IP subnet of your trusted User Agents (UAs).

Correct Answer: BC

---

#### QUESTION 4

What should you do to enable physical interface redundancy?

- A. Navigate to the system-config configuration element and set the phy-redundancy parameter to enabled.
- B. Navigate to the network-interface configuration element and set the phy-redundancy parameter to enabled.
- C. Navigate to the network-interface configuration element and set the link-redundancy- state parameter to enabled.
- D. Navigate to the system-config configuration element and set the link-redundancy-state parameter to enabled.
- E. Run the superuser command enable phy-redundancy.

Correct Answer: C

---

#### QUESTION 5

To return the Session Border Controller configuration to a known, factory default state, you must\_\_\_\_\_.

- A. press the reset button on the front panel
- B. issue the delete-config command
- C. issue the set-system-state offline command
- D. issue the set-system-state offline
- E. issue the delete-config and reboot commands

Correct Answer: E

[1Z0-404 PDF Dumps](#)

[1Z0-404 VCE Dumps](#)

[1Z0-404 Study Guide](#)