



1Z0-816^{Q&As}

Java SE 11 Programmer II

Pass Oracle 1Z0-816 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1z0-816.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Given:

```
jdeps -jdkinternals C:\workspace4\SimpleSecurity\jar\classes.jar
```

Which describes the expected output?

- A. jdeps lists the module dependencies and the package names of all referenced JDK internal APIs. If any are found, the suggested replacements are output in the console.
- B. jdeps outputs an error message that the -jdkinternals option requires either the -summary or the verbose options to output to the console.
- C. The -jdkinternals option analyzes all classes in the .jar and prints all class-level dependencies.
- D. The -jdkinternals option analyzes all classes in the .jar for class-level dependencies on JDK internal APIs. If any are found, the results with suggested replacements are output in the console.

Correct Answer: A

-jdkinternals option analyzes all classes in the .jar for class-level dependencies on JDK internal APIs. If any are found, the results with suggested replacements are output in the console.

QUESTION 2

Given:

```
public class Tester {
    static class Person implements /* line 1 */ {
        private String name;
        Person(String name) { this.name = name; }
        /* line 2 */
    }
    public static void main(String[] args) {
        Person[] people = {new Person("Joe"),
                           new Person("Jane"),
                           new Person("John")};
        Arrays.sort(people);
        for(Person person: people) {
            System.out.println(person.name);
        }
    }
}
```

You want the code to produce this output:

John
Joe
Jane



Which code fragment should be inserted on line 1 and line 2 to produce the output?

- A. Insert Comparator on line 1. Insert `public int compare(Person p1, Person p2) { return p1.name.compare(p2.name); }` on line 2.
- B. Insert Comparator on line 1. Insert `public int compareTo(Person person) { return person.name.compareTo(this.name); }` on line 2.
- C. Insert Comparable on line 1. Insert `public int compare(Person p1, Person p2) { return p1.name.compare(p2.name); }` on line 2.
- D. Insert Comparator on line 1. Insert `public int compare(Person person) { return person.name.compare(this.name); }` on line 2.

Correct Answer: B

Reference: <https://www.coursehero.com/file/p320ss6/Override-public-int-compareTo-Person-otherCompare-this-objects-name-to-others/>

QUESTION 3



```
1 import java.util.*;
2 import java.io.*;
3 import java.lang.Thread;
4 import java.util.ArrayList;
5 import java.util.LinkedList;
6 import java.util.List;
7 import java.util.function.Consumer;
8 import java.util.stream.Stream;
9 import java.util.stream.IntStream;
10
11
12 public class Main {
13
14     public static void main(String[] args) {
15         int arr[][] = {{5,10}, {8,12}, {9,3}};
16         long count = Stream.of(arr)
17             .flatMapToInt(IntStream::of)
18             .map (n -> n + 1)
19             .filter(n -> (n % 2 == 0))
20             .peek(System.out::print)
21             .count();
22         System.out.println(" " + count);
23     }
24 }
```

Execute Mode, Version, Inputs & Arguments

JDK 11.0.4

CommandLine Arguments

Result

CPU Time: 0.32 sec(s), Memory: 34220 kilobyte(s)

6104 3

Which is a proper JDBC URL?

- A. jdbe.mysql.com://localhost:3306/database
- B. http://localhost.mysql.com:3306/database
- C. http://localhost mysql.jdbc:3306/database
- D. jdbc:mysql://localhost:3306/database



Correct Answer: D

Reference: <https://vladmihalcea.com/jdbc-driver-connection-url-strings/>

QUESTION 4

```
sample.java
1 import java.util.*;
2 import java.io.*;
3 import java.util.stream.Stream;
4 import java.lang.String;
5 import java.util.List;
6 import java.util.function.BinaryOperator;
7
8 import java.util.Scanner;
9
10 public class sample{
11     public static void main (String[] args)
12     {
13         try (BufferedReader in = new BufferedReader(new InputStreamReader(System.in)))
14         {
15             System.out.print("Input:");
16             String input = in.readLine();
17             System.out.print("Input:" + input);
18         }
19         catch (IOException e)
20         {e.printStackTrace();}
21     }
}
```

Console 10
Input:

Given:

```
public class X { }
```

```
and public final class Y extends X { }
```

What is the result of compiling these two classes?

- A. The compilation fails because there is no zero args constructor defined in class X.
- B. The compilation fails because either class X or class Y needs to implement the toString() method.
- C. The compilation fails because a final class cannot extend another class.
- D. The compilation succeeds.

Correct Answer: B

QUESTION 5

Given:



```
public class Hello {  
    class Greeting {  
        void sayHi() {  
            System.out.println("Hello world");  
        }  
    }  
    public static void main(String... args) {  
        // Line 1  
    }  
}
```

What code must you insert on Line 1 to enable the code to print Hello world?

- A. Hello.Greeting myG = new Hello.Greeting() myG.sayHi();
- B. Hello myH = new Hello(); Hello.Greeting myG = myH.new Greeting(); myG.sayHi();
- C. Hello myH = new Hello(); Hello.Greeting myG = myH.new Hello.Greeting(); myG.sayHi();
- D. Hello myH = new Hello(); Greeting myG = new Greeting(); myG.sayHi ();

Correct Answer: B

[Latest 1Z0-816 Dumps](#)

[1Z0-816 PDF Dumps](#)

[1Z0-816 VCE Dumps](#)