



1Z0-888^{Q&As}

MySQL 5.7 Database Administrator

Pass Oracle 1Z0-888 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/1z0-888.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

A MySQL instance has this configuration values set:

```
--innodb-doublewrite=ON  
--innodb-flush-log-at-trx-commit=1  
--sync-binlog=1
```

A transaction involving a single InnoDB INSERT statement commits. Which list of locations is in the sequence of disk writes for this transaction?

- A. binary log, redo log, doublewrite buffer, and tablespace
- B. redo log, binary log, doublewrite buffer, and tablespace
- C. doublewrite buffer, redo log, tablespace, and binary log
- D. redo log, doublewrite buffer, tablespace, and binary log

Correct Answer: A

QUESTION 2

Why should you be selective when granting the PROCESS privilege to an account?

- A. It allows a client to process scripts.
- B. It allows the use of stored routines.
- C. It allows a client to see another user's queries with the SHOW PROCESSLIST command.
- D. It allows a client to control running processes on a server.

Correct Answer: D

Reference: <https://dev.mysql.com/doc/refman/8.0/en/privileges-provided.html>

QUESTION 3

You are using GTIDS in replication. You need to skip a transaction with the GTID of aaa-bbb-ccc-dddeee:3 on a slave.

Which procedure would you execute from a MySQL prompt?



- A. `STOP SLAVE;`
`SET GLOBAL SQL_SLAVE_SKIP_COUNTER=1;`
`START SLAVE;`
- B. `STOP SLAVE;`
`SET GTID_NEXT='aaa-bbb-ccc-ddd-eee:3';`
`BEGIN;`
`COMMIT;`
`SET GTID_NEXT='AUTOMATIC';`
`START SLAVE`
- C. `STOP SLAVE;`
`RESET SLAVE;`
`BEGIN;`
`SKIP NEXT GTID;`
`COMMIT;`
`START SLAVE;`
- D. `STOP SLAVE;`
`BEGIN;`
`SET GTID_IGNORE='aaa-bbb-ccc-ddd-eee:3';`
`COMMIT;`
`START SLAVE;`

A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: B

QUESTION 4

Host slave1 has ip address 192.0.2.10. Host slave2 has ip address 203.0.113.50

Examine these commands:



```
shell> mysql_config_editor print --all
[slave1]
host = slave1.exampledomain.com
user=robert
[slave2]
host = slave2.exampledomain.com
user=karen

shell> mysql --login-path=slave1 --host=192.0.2.10 --
user=robert -p
Enter password:
ERROR 1045 (28000): Access denied for user
'robert'@'192.0.2.10' (using password: YES)
```

Why did this error occur?

- A. The host on the command line is not defined in the login path.
- B. The mysqld instance has not been restarted after creating the login path.
- C. There is no password defined in the login path.
- D. The DNS is not configured correctly for slave1 host.
- E. The .mylogin.cnf file is not readable.

Correct Answer: E

QUESTION 5

old_alter_table is disabled as shown. mysql> SELECT @@old_alter_table;

```
+-----+
| @@old_alter_table |
+-----+
| 0                |
+-----+

1 row in set (0.00 sec)
```



Consider this statement on a RANGE-partitioned table: `mysql> ALTER TABLE orders DROP PARTITION p1, p3;` What is the outcome of executing this statement?

- A. All data in p1 and p3 partitions is removed and the table definition is changed.
- B. All data in p1 and p3 partitions is removed, but the table definition remains unchanged.
- C. Only the first partition (p1) will be dropped because only one partition can be dropped at any time.
- D. It results in a syntax error because you cannot specify more than one partition in the same statement.

Correct Answer: B

[1Z0-888 PDF Dumps](#)

[1Z0-888 VCE Dumps](#)

[1Z0-888 Practice Test](#)