



# 210-250<sup>Q&As</sup>

Cisco Cybersecurity Fundamentals

**Pass Cisco 210-250 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/210-250.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Which one of the following options is the MAC address that a host would use to send broadcast messages if its own MAC address is 0800:0222:2222?

- A. 0000:0000:0000
- B. 0800:0222:FFFF
- C. 0800:FFFF:FFFF
- D. FFFF:FFFF:FFFF

Correct Answer: D

---

### QUESTION 2

What is the difference between brute-forcing and password spraying?

- A. Brute-forcing refers to extracting AES keys from memory, and password spraying is attempting all possible passwords from a dictionary of common passwords.
- B. Brute-forcing is calculating the most likely password for a user, based on the user's birthday, anniversary, and children's birthdays. Password spraying means to try every password based on a dictionary.
- C. Brute-forcing is coercing users to give you their password, and password spraying refers to gathering credentials through phishing campaigns.
- D. Brute-forcing is an attempt of every possible password on certain accounts, and password spraying is attempting only a couple common passwords on every possible account.

Correct Answer: D

---

### QUESTION 3

Which of the following is not a disadvantage of host-based antimalware?

- A. It requires updating multiple endpoints.
- B. It does not have visibility into encrypted traffic.
- C. It does not have visibility of all events happening in the network.
- D. It may require working with different operating systems.

Correct Answer: B

---

### QUESTION 4



What is one way of mitigating DHCP attacks by using a Cisco switch?

- A. VLAN segmentation
- B. MAC address security
- C. DHCP snooping
- D. DHCP authentication

Correct Answer: C

---

#### QUESTION 5

What is one result of placing an IPS on the untrusted (outside) segment of a firewall?

- A. The IPS can collect and correlate raw data from other network devices such as firewalls.
- B. The IPS alerts include real IP addresses rather than NATed addresses.
- C. The IPS generates more true positive alerts.
- D. The IPS can detect new forms of attacks.

Correct Answer: D

[Latest 210-250 Dumps](#)

[210-250 PDF Dumps](#)

[210-250 Study Guide](#)