

# 2V0-41.19<sup>Q&As</sup>

VMware Professional NSX-T Data Center 2.4

## Pass VMware 2V0-41.19 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.geekcert.com/2v0-41-19.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by VMware Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



## https://www.geekcert.com/2v0-41-19.html

### 2024 Latest geekcert 2V0-41.19 PDF and VCE dumps Download

#### **QUESTION 1**

Which two CLI commands could be used to see if vmnic link status is down? (Choose two.)

- A. esxcli network vswitch dvs vmware list
- B. esxcfg-nics -1
- C. esxcfg-vmsvc/get.networks
- D. esxcfg-vmknic -1
- E. esxcli network nic list

Correct Answer: AE

#### **QUESTION 2**

Which NSX CLI command is used to check the GENEVE tunnel status on ESXi transport node?

- A. get host-switch tunnels
- B. get host-switch tunnel status
- C. get transport-node tunnel state
- D. get transport-node tunnel status

Correct Answer: A

#### **QUESTION 3**

Which three hardware-based offloads provide maximum performance for physical network interface cards? (Choose three.)

- A. Netfilter Flow Offload (NFO)
- B. Priority Flow Control (PFC)
- C. Receive Side Scaling (RSS)
- D. TCP Segmentation Offload (TSO)
- E. Source Route Bridging (SRB)
- F. Large Receive Offload (LRO)

## https://www.geekcert.com/2v0-41-19.html

2024 Latest geekcert 2V0-41.19 PDF and VCE dumps Download

Correct Answer: CDF

#### **QUESTION 4**

In a NSX-T Data Center environment, an administrator is observing low throughput and congestion between the Tier-0 Gateway and the upstream physical routers.

Which two actions could address low throughput and congestion? (Choose two.)

- A. Configure a Tier-1 gateway and connect it directly to the physical routers.
- B. Configure ECMP on the Tier-0 gateway.
- C. Configure NAT on the Tier-0 gateway.
- D. Deploy Large size Edge node/s.
- E. Add an additional vNIC to the NSX Edge node.

Correct Answer: BD

#### **QUESTION 5**

What is required to configure a load balancer in inline mode?

- A. DNAT
- B. SNAT
- C. Client and server connected to different Tier-1 Gateways
- D. Client and server running on different transport nodes

Correct Answer: C

Latest 2V0-41.19 Dumps

2V0-41.19 VCE Dumps

2V0-41.19 Exam Questions