



2V0-641^{Q&As}

VMware Certified Professional 6 – Network Virtualization Beta

Pass VMware 2V0-641 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/2v0-641.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which NSX component can validate that security policies at your organization are being enforced correctly?

- A. Activity Monitoring
- B. Flow Monitoring
- C. ERSPAN
- D. Distributed firewalls

Correct Answer: A

QUESTION 2

A vSphere administrator wants to setup an NSX Edge Service Gateway to provide traveling employees secure access to company servers located in specific network segments within the corporate Data Centers.

The solution has to be as scalable as possible.

Which Virtual Private Network solution will satisfy the administrator's requirements?

- A. SSL VPN
- B. MPLS VPN
- C. Layer 2 VPN
- D. IPSec VPN

Correct Answer: A

QUESTION 3

What is the minimum number of vSphere Distributed Switches (vDS) that must be configured before deploying VMware NSX for vSphere?

- A. 0
- B. 1
- C. 2
- D. 4

Correct Answer: B



QUESTION 4

An NSX Edge Service Gateway has two interfaces:

Internal interface named Internal Access -- IP address = 10.10.10.1 -- Network mask = 255.255.255.0

Uplink interface named Physical Uplink -- IP address = 20.20.20.1 -- Network mask = 255.255.255.0 A vSphere administrator wants to add a SNAT rule to allow traffic from the internal network segment to

access external resources via the uplink interface.

Which three steps should the vSphere administrator do to add the SNAT rule? (Choose three.)

- A. Apply the SNAT rule to the Internal Access interface.
- B. Select 10.10.10.1 as the translated source IP.
- C. Apply the SNAT rule on the Physical Uplink interface.
- D. Select 10.10.10.0/24 as the original subnet.
- E. Choose 20.20.20.2 as the translated source IP address.

Correct Answer: CDE

QUESTION 5

An administrator wishes to control traffic flow between two virtual machines. The virtual machines are in the same subnet, but are located on separate ESXi hosts. The administrator deploys an Edge Firewall to one of the hosts and verifies the default firewall rule is set to deny, but the two virtual machines can still communicate with each other.

What task will correct this issue?

- A. Configure both ESXi host firewalls to deny traffic from the virtual machine on the other host.
- B. Deploy another Edge Firewall on the host running the second virtual machine.
- C. Remove any other firewall appliances that may exist on either of the ESXi hosts.
- D. Deploy a Distributed Firewall with firewall rules to prevent traffic between the virtual machines.

Correct Answer: D

[Latest 2V0-641 Dumps](#)

[2V0-641 VCE Dumps](#)

[2V0-641 Study Guide](#)