

300-365^{Q&As}

Deploying Cisco Wireless Enterprise Networks

Pass Cisco 300-365 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.geekcert.com/300-365.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



VCE & PDF GeekCert.com

https://www.geekcert.com/300-365.html

2021 Latest geekcert 300-365 PDF and VCE dumps Download

QUESTION 1

Which option is a calibration of a Cisco MSE deployment limited to when that deployment is using the linear point collection method?

- A. rogue AP
- B. associated 802.11 a/n clients
- C. RFID tag
- D. associated 802.11 b/g/n clients

Correct Answer: A

 $Reference: https://www.cisco.com/c/en/us/td/docs/wireless/mse/8-0/MSE_CMX/8_0_MSE_CAS/7_4_MSE_CAS_chapter_01010.html$

QUESTION 2

An enterprise has experienced several incidents of clients running out of IP addresses while in a stadium. Which kind of group can be implemented to help more clients access the network?

- A. FlexConnect
- B. AP
- C. interface
- D. WLAN

Correct Answer: A

QUESTION 3

An engineer has found that voice traffic on the WLAN with ID XXXXXXXXX is being sent at best effort from a client that is experiencing issues despite having QoS and CAC enabled. Which option causes the traffic to be sent at best effort?

- A. The QoS profile for Platinum has been left at default settings.
- B. The client does not support TSPEC.
- C. WMM is configured as required.
- D. msl qos trust cos is not configured on the switchport.

Correct Answer: B

QUESTION 4



https://www.geekcert.com/300-365.html

2021 Latest geekcert 300-365 PDF and VCE dumps Download

Which two parameters must be considered when conducting an outdoor mesh site survey? (Choose two.)

A. weather

B. traffic lights

C. throughput

D. Fresnel zone

E. near-far effect

Correct Answer: AD

QUESTION 5

An engineer must ensure that the number of clients on a WLAN does not exceed the available number of IP addresses that are allocated to the network. Which command ensures that a full/24 network does not associate at one time?

A. config interface nat-address management enable

B. config interface address dynamic-interface client 192.168.1.2 255.255.254.0 192.168.1.1

C. config wlan max-associated-clients 250

D. config wlan max-radio-clients 250

Correct Answer: C

Latest 300-365 Dumps

300-365 Practice Test

300-365 Study Guide



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.geekcert.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited. All trademarks are the property of their respective owners. Copyright © geekcert, All Rights Reserved.