



300-430^{Q&As}

Implementing Cisco Enterprise Wireless Networks (ENWLSI)

Pass Cisco 300-430 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/300-430.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which two statements about the requirements for a Cisco Hyperlocation deployment are true? (Choose two.)

- A. After enabling Cisco Hyperlocation on Cisco CMX, the APs and the wireless LAN controller must be restarted.
- B. NTP can be configured, but that is not recommended.
- C. The Cisco Hyperlocation feature must be enabled on the wireless LAN controller and Cisco CMX.
- D. The Cisco Hyperlocation feature must be enabled only on the wireless LAN controller.
- E. If the Cisco CMX server is a VM, a high-end VM is needed for Cisco Hyperlocation deployments.

Correct Answer: CE

<https://www.cisco.com/c/en/us/products/collateral/wireless/mobility-services-engine/datasheet-c78-734648.html>

QUESTION 2

An engineer is implementing a FlexConnect group for access points at a remote location using local switching but central DHCP. Which client feature becomes available only if this configuration is changed?

- A. multicast
- B. static IP
- C. fast roaming
- D. mDNS

Correct Answer: B

https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-7/configguide/b_cg87/flexconnect.html After 3 failed attempts the static Ip is given.

QUESTION 3

An engineer is in the process of implementing Fastlane on a wireless network with a Mobility Express AP installed. The network must support voice and video applications for Apple devices. Due to a security concern, all iPhones are updated to version 14.5.432302546. Which QoS profile must the engineer configure on the user WLAN?

- A. Bronze
- B. Best Effort
- C. Silver
- D. Platinum

Correct Answer: D



Ref: https://www.cisco.com/c/dam/en/us/td/docs/wireless/controller/technotes/8-3/Optimizing_WiFi_Connectivity_and_Prioritizing_Business_Apps.pdf

QUESTION 4

A network engineer is implementing BYOD on a wireless network. Based on the customer requirements, a dual SSID approach must be taken. Which two advanced WLAN configurations must be performed? (Choose two.)

- A. Set Allow AAA Override to Enabled.
- B. Select DHCP Profiling.
- C. Set DHCP Addr. Assignment to Required.
- D. Set NAC State to Radius NAC.
- E. Select Enable Session Timeout.

Correct Answer: AD

QUESTION 5

Which of following feature on the Cisco Wireless LAN Controller must be present to support dynamic VLAN mapping?

- A. AAA override
- B. CCKM/OKC
- C. FlexConnect ACL
- D. VLAN name override

Correct Answer: A

[300-430 PDF Dumps](#)

[300-430 Practice Test](#)

[300-430 Exam Questions](#)