



300-430^{Q&As}

Implementing Cisco Enterprise Wireless Networks (ENWLSI)

Pass Cisco 300-430 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/300-430.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

An engineer must implement Cisco Identity-Based Networking Services at a remote site using ISE to dynamically assign groups of users to specific IP subnets. If the subnet assigned to a client is available at the remote site, then traffic must be offloaded locally, and subnets are unavailable at the remote site must be tunneled back to the WLC. Which feature meets these requirements?

- A. learn client IP address
- B. FlexConnect local authentication
- C. VLAN-based central switching
- D. central DHCP processing

Correct Answer: C

https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-5/Enterprise-Mobility-8-5-Design-Guide/Enterprise_Mobility_8-5_Deployment_Guide/ch7_HREA.html

QUESTION 2

A network engineer is configuring a Cisco AireOS WLC environment for central web authentication using Cisco ISE.

The controllers are configured using auto-anchor for the guest network.

Which three components must be implemented for the foreign WLC?(Choose three.)

- A. DHCP RADIUS profiling enabled.
- B. HTTP RADIUS profiling enabled.
- C. UDP/1812-1813 open to ISE
- D. downloadable preauth ACL on ISE
- E. local preauth ACL on WLC
- F. WLAN Layer 2 security

Correct Answer: ACF

QUESTION 3

Refer to the exhibit.



General	Security	QoS	Policy-Mapping	Advanced																
Maximum Allowed Clients Per AP Radio		<input type="text" value="200"/>																		
Clear HotSpot Configuration		<input type="checkbox"/> Enabled																		
Client user idle timeout(15-100000)		<input type="checkbox"/>																		
Client user idle threshold (0-10000000)		<input type="text" value="0"/> Bytes																		
Radius NAI-Realm		<input type="checkbox"/>																		
11ac MU-MIMO		<input checked="" type="checkbox"/>																		
Off Channel Scanning Defer																				
Scan Defer Priority		<table border="1"><tr><td>0</td><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td><td><input type="checkbox"/></td></tr></table>			0	1	2	3	4	5	6	7	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
0	1	2	3	4	5	6	7													
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>													
Scan Defer Time(msecs)		<input type="text" value="100"/>																		
FlexConnect																				
FlexConnect Local Switching ²		<input type="checkbox"/> Enabled																		
FlexConnect Local Auth ¹²		<input type="checkbox"/> Enabled																		
Learn Client IP Address ⁵		<input checked="" type="checkbox"/> Enabled																		

A customer has implemented Cisco FlexConnect deployments with different WLANs around the globe and is opening a new branch in a different location. The engineer's task is to execute all the wireless configuration and to suggest how to configure the switch ports for new APs. Which configuration must the switching team use on the switch port?

- A. Multiple VLAN
- B. Access mode
- C. Trunk mode
- D. Single mode

Correct Answer: C



QUESTION 4

Where is Cisco Hyperlocation enabled on a Cisco Catalyst 9800 Series Wireless Controller web interface?

- A. Policy Profile
- B. AP Join Profile
- C. Flex Profile
- D. RF Profile

Correct Answer: B

https://www.cisco.com/c/en/us/td/docs/wireless/controller/9800/config-guide/b_wl_16_10_cg/cisco-hyperlocation.html

QUESTION 5

Refer to the exhibit.

MONITOR WLANs CONTROLLER WIRELESS SECURITY MANAGEMENT COMMANDS HELP FEEDBACK								
Access Control Lists > Edit								
General								
Access List Name		ACL_Provisioning_Redirect						
Seq	Action	Source IP/Mask		Destination IP/Mask		Protocol	Source Port	Dest Port
1	Permit	0.0.0.0	/ 0.0.0.0	10.230.1.45	/ 255.255.255.255	Any	Any	Any
2	Permit	10.230.1.45	/ 255.255.255.255	0.0.0.0	/ 0.0.0.0	Any	Any	Any
3	Permit	0.0.0.0	/ 0.0.0.0	10.225.49.15	/ 255.255.255.255	Any	Any	Any
4	Permit	10.225.49.15	/ 255.255.255.255	0.0.0.0	/ 0.0.0.0	Any	Any	Any
5	Permit	0.0.0.0	/ 0.0.0.0	10.230.1.61	/ 255.255.255.255	UDP	DHCP Client	DHCP Server
6	Permit	10.230.1.61	/ 255.255.255.255	0.0.0.0	/ 0.0.0.0	UDP	DHCP Server	DHCP Client
7	Permit	0.0.0.0	/ 0.0.0.0	173.194.0.0	/ 255.255.0.0	Any	Any	Any
8	Permit	173.194.0.0	/ 255.255.0.0	0.0.0.0	/ 0.0.0.0	Any	Any	Any
9	Permit	0.0.0.0	/ 0.0.0.0	74.125.0.0	/ 255.255.0.0	Any	Any	Any
10	Permit	74.125.0.0	/ 255.255.0.0	0.0.0.0	/ 0.0.0.0	Any	Any	Any
11	Deny	0.0.0.0	/ 0.0.0.0	0.0.0.0	/ 0.0.0.0	Any	Any	Any

An ACL is configured to restrict access for BYOD clients. The ACL must redirect devices to the guest portal. To which two devices on the local network must the ACL allow access other than the DHCP server? (Choose two.)

- A. SNMP server
- B. Cisco ISE
- C. DNS server
- D. WLCD
- E. RADIUS server

Correct Answer: BC



VCE & PDF

GeekCert.com

<https://www.geekcert.com/300-430.html>

2024 Latest geekcert 300-430 PDF and VCE dumps Download

[Latest 300-430 Dumps](#)

[300-430 Exam Questions](#)

[300-430 Braindumps](#)