



300-430^{Q&As}

Implementing Cisco Enterprise Wireless Networks (ENWLSI)

Pass Cisco 300-430 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/300-430.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Refer to the exhibit.

```
(Cisco Controller) >show nmsp notification interval

NMSP Notification Interval Summary

RSSI Interval:
Client..... 20 sec
RFID..... 20 sec
Rogue AP..... 20 sec
Rogue Client..... 20 sec

Spectrum Interval:
Interferer device..... 20 sec

(Cisco Controller) >
```

An administrator notices slower location updates from the controller to Cisco CMX. Which command must be configured to get an update every 5 seconds for rogues?

- A. config location notification interval rssi rogues 5
- B. config nmsp notification interval rssi rogues 5
- C. config subscription notification interval rssi rogues 5
- D. config cmx notification interval rssi rogues 5

Correct Answer: B

[https://www.cisco.com/c/en/us/td/docs/wireless/controller/9800/17-6/config-guide/b_wl_17_6_cg/m_ewlc_nmsp.html#task_C2454AC7B1B14E19899B48489EF24304~:text=Example%3A-,Device\(config\)%23%20nmsp%20notification%20interval%20rssi%20rfid%2050,-Sets%20the%20NMSP](https://www.cisco.com/c/en/us/td/docs/wireless/controller/9800/17-6/config-guide/b_wl_17_6_cg/m_ewlc_nmsp.html#task_C2454AC7B1B14E19899B48489EF24304~:text=Example%3A-,Device(config)%23%20nmsp%20notification%20interval%20rssi%20rfid%2050,-Sets%20the%20NMSP)

QUESTION 2

A company is collecting the requirements for an on-premises event. During the event, a wireless client connected to a dedicated WLAN will run a video application that will need to average 300000000 bits per second to function properly. What is the QoS marketing that needs to be applied to that WLAN?

- A. Bronze
- B. Platinum
- C. Silver



D. Gold

Correct Answer: D

QUESTION 3

Refer to the exhibit.

802.11a(5 GHz) > Media

Voice Video **Media**

Call Admission Control (CAC)

Admission Control (ACM)	<input checked="" type="checkbox"/> Enabled
CAC Method <u>4</u>	Load Based ▾
Max RF Bandwidth (5-85) (%)	75
Reserved Roaming Bandwidth (0-25) (%)	6
Expedited bandwidth	<input type="checkbox"/>
SIP CAC Support <u>3</u>	<input type="checkbox"/> Enabled

Per-Call SIP Bandwidth 2

SIP Codec	G.711 ▾
SIP Bandwidth (kbps)	64
SIP Voice Sample Interval (msecs)	20 ▾

Which two items must be supported on the VoWLAN phones to take full advantage of this WLAN configuration? (Choose two.)

- A. TSPEC
- B. SIFS
- C. 802.11e
- D. WMM



E. APSD

Correct Answer: CD

The 802.11e, WMM, and Cisco Compatible Extension specifications help balance and prevent the overloading of a cell with audio streams. CAC determines whether there is enough channel capacity to start a call; if not, the phone can scan for another channel https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-1/Enterprise-Mobility-8-1-Design-Guide/Enterprise_Mobility_8-1_Deployment_Guide/Chapter-9.html

QUESTION 4

A FlexConnect remote office deployment is using five 2702i APs indoors and two 1532i APs outdoors. When a code upgrade is performed and FlexConnect Smart AP Image Upgrade is leveraged, but no FlexConnect Master AP has been configured, how many image transfers between the WLC and APs will occur?

- A. 1
- B. 2
- C. 5
- D. 7

Correct Answer: B

"A FlexConnect group can have one primary AP per AP model. If a primary AP is not selected manually, the AP that has the least MAC address value is automatically chosen as the primary AP for that model."

QUESTION 5

An engineer is deploying a virtual MSE. The network has 3000 APs and needs 7000 IPS licenses. To which size server does the engineer scale it?

- A. virtual
- B. standard
- C. high end
- D. low end

Correct Answer: C

[Latest 300-430 Dumps](#)

[300-430 PDF Dumps](#)

[300-430 Braindumps](#)