



300-435^{Q&As}

Automating and Programming Cisco Enterprise Solutions (ENAUTO)

Pass Cisco 300-435 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/300-435.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

"https://vmanage-ip-address:8443/dataservice/template/policy/vsmart/activate/{policyId}"

Refer to the exhibit. A Python script must be created to deactivate vSmart Policy Cisco SD-WAN vManage Configuration APIs. The documentation states the URL is as shown in the exhibit for this REST call using POST, and that "policyId" is a required request parameter. Which line of Python code makes this call, assuming the variable "s" is a valid Requests session object and the variable "policy-id" is the policyId?

- A. `s.port('https://vmanage:8443/dataservice/template/policy/vsmart/activate?policyId=%s' % policy_id)`
- B. `s.port('https://vmanage:8443/dataservice/template/policy/vsmart/activate/%s' % policy_id)`
- C. `s.port('https://vmanage:8443/dataservice/template/policy/vsmart/activateandpolicyId=%s' % policy_id)`
- D. `s.port('https://vmanage:8443/dataservice/template/policy/vsmart/activate/', data = {'policyId': policy_id})`

Correct Answer: A

QUESTION 2

Which two Cisco DNA center features are needed to add legacy on the platform? (Choose two.)

- A. Multivendor SDK support
- B. Trusted device profile update
- C. Device package creation
- D. Device package download
- E. Device profile replication

Correct Answer: AD

QUESTION 3

Which setting is used for the dampening period when configuring an on-change publication for YANG-push versus OpenConfig?

- A. null
- B. -1
- C. 0
- D. 1000

Correct Answer: C



Reference: https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/prog/configuration/1612/b_1612_programmability_cg/model_driven_telemetry.html

QUESTION 4

```
{
  "version": "1.0",
  "response": [
    {
      "time": "2019-07-15T19:10:00.000+0000",
      "healthScore": 73,
      "totalCount": 11,
      "goodCount": 8,
      "unmonCount": 3,
      "fairCount": 0,
      "badCount": 0,
      "entity": null,
      "timeInMillis": 1563217800000
    }
  ],
  "measuredBy": "global",
  "latestMeasuredByEntity": null,
  "latestHealthScore": 73,
  "monitoredDevices": 8,
  "monitoredHealthyDevices": 8,
  "monitoredUnHealthyDevices": 0,
  "unMonitoredDevices": 3,
  "healthDistribution": [
    {
      "category": "Access",
      "totalCount": 9,
      "healthScore": 100,
      "goodPercentage": 100,
      "badPercentage": 0,
      "fairPercentage": 0,
      "unmonPercentage": 0,
      "goodCount": 3,
      "badCount": 0,
      "fairCount": 0,
      "unmonCount": 0
    },
    {
      "category": "Distribution",
      "totalCount": 2,
      "healthScore": 100,
      "goodPercentage": 100,
      "badPercentage": 0,
      "fairPercentage": 0,
      "unmonPercentage": 0,
      "goodCount": 2,
      "badCount": 0,
      "fairCount": 0,
      "unmonCount": 0
    },
    {
      "category": "WLC",
      "totalCount": 2,
      "healthScore": 50,
      "goodPercentage": 0,
      "badPercentage": 0,
      "fairPercentage": 0,
      "unmonPercentage": 100,
      "goodCount": 1,
      "badCount": 0,
      "fairCount": 0,
      "unmonCount": 1
    }
  ]
}
```

Refer to the exhibit. Which device type is functioning in a degraded state?

- A. access point
- B. distribution switch



C. access switch

D. wireless LAN controller

Correct Answer: C

QUESTION 5

DRAG DROP

Drag and drop the commands to the Ansible playbook that applies configuration to an interface on a Cisco IOS XE device. Not all options are used.

Select and Place:

Answer Area

ioscmd	interface
parents	iosxe
iosconfig	ios_config

```
- name: configure interface settings
  [ ]:
    lines:
      -ip address 172.31.1.1 255.255.255.0
      -no shutdown
  [ ]: interface GigabitEthernet1/0
```

Correct Answer:

Answer Area

ioscmd	interface
[]	iosxe
iosconfig	[]

```
- name: configure interface settings
  ios_config:
    lines:
      -ip address 172.31.1.1 255.255.255.0
      -no shutdown
  [ ]: interface GigabitEthernet1/0
```

Reference: <http://imxing.cn/?p=464>

[Latest 300-435 Dumps](#)

[300-435 Practice Test](#)

[300-435 Exam Questions](#)