



300-435^{Q&As}

Automating and Programming Cisco Enterprise Solutions (ENAUTO)

Pass Cisco 300-435 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/300-435.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

DRAG DROP

Drag and drop the characteristic from the left onto the monitoring type described on the right.

Select and Place:

Answer Area

- Troubleshoot instant high spikes of CPU and memory load on network devices.
- Ask network devices for any metric at any time.
- Prevent network devices from listening for network connections.
- Minimize the work required by device agents by pushing data as soon as the data is generated.

Streaming Telemetry

Traditional Network Monitoring

Correct Answer:

Answer Area

Streaming Telemetry

- Troubleshoot instant high spikes of CPU and memory load on network devices.
- Ask network devices for any metric at any time.
- Prevent network devices from listening for network connections.

Traditional Network Monitoring

- Minimize the work required by device agents by pushing data as soon as the data is generated.

Reference: https://www.cisco.com/c/en/us/td/docs/iosxr/ncs5500/telemetry/70x/b-telemetry-cg-ncs5500-70x/b-telemetry-cg-ncs5500-70x_chapter_010.html



QUESTION 2

Which field must be completed in Cisco DNA Center when a network discovery is initiated?

- A. SNMP read community string
- B. Enable password
- C. NETCONF port
- D. Discovery type

Correct Answer: D

Reference: https://www.cisco.com/c/dam/en_us/training-events/product-training/dnac-13/DNAC13_AddingDevicesByUsingDiscovery.pdf (p.26)

QUESTION 3

```
1 {
2   'data':
3     [
4       {
5         'count':4,
6         'detailsURL': '',
7         'name': 'vEdge Hardware Health',
8         'status': 'error',
9         'statusList':
10          [
11            {
12              'count':4
13              'detailsURL': '/dataservice/device/hardwarehealth/detail?state=normal',
14              'message': '4 (normal=4, warning=0,error=0)',
15              'name': 'normal',
16              'status': 'up'
17            }
18          ]
19       }
20     ]
21 }
```

Refer to the exhibit. Cisco SD-WAN deployment must be fixed using vManage APIs. A call to vEdge Hardware Health API returns the data in the exhibit (only a portion is shown). If the JSON shown in the exhibit is converted to a Python dictionary named "d", how is the "status" property referenced?

- A. d['data']['statusList']['status']
- B. nbvnbvnbhg
- C. d['data'][0]['statusList'][0]['status']
- D. d[data][0][statusList][0][status]

Correct Answer: C



QUESTION 4

What does Cisco DNA Center use to manage third-party devices?

- A. command runners
- B. multivendor SDK
- C. templates
- D. device packages

Correct Answer: D

Reference: <https://developer.cisco.com/docs/dna-center/>

QUESTION 5

What is primary purpose of using the Cisco SD-WAN vManage Certificate Management API?

- A. to securely deploy vManage
- B. to report an issue to Cisco TAC
- C. to install signed certificates
- D. to contact Enterprise Certificate Authority

Correct Answer: A

Reference: https://sdwan-docs.cisco.com/Product_Documentation/vManage_Help/Release_17.1/Configuration/Certificates

[300-435 VCE Dumps](#)

[300-435 Exam Questions](#)

[300-435 Braindumps](#)