



# 300-625<sup>Q&As</sup>

Implementing Cisco Storage Area Networking (DCSAN)

## Pass Cisco 300-625 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/300-625.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

A network engineer is configuring a Cisco MDS switch for FCoE. Which two conditions must be considered during the implementation phase? (Choose two.)

- A. On Cisco MDS switches, system-defined class maps for class-FCoE and class-default are enabled but can be deleted.
- B. The QoS policy must be identical to other Cisco FCoE switches in the network.
- C. On the Cisco MDS, the MTU is set equal to 2112.
- D. VLAN 1 or the native VLAN can be mapped to an FCoE VSAN.
- E. FCoE is already enabled on a Cisco MDS switch.

Correct Answer: BE

---

### QUESTION 2

Which result occurs when a VSAN is deleted that contains non-trunking ports?

- A. The ports are moved to VSAN 4094.
- B. The ports are moved to VSAN 1.
- C. The ports are removed from the configuration.
- D. The port configurations are cleared.

Correct Answer: A

---

### QUESTION 3

A storage network engineer is implementing disk-array data replication between two SAN environments in two different data centers not connected via Fibre Channel. Which SAN switch feature must be implemented?

- A. FCIP
- B. zoning merge over LAN
- C. VSAN scoping
- D. IVR

Correct Answer: A

---

### QUESTION 4



A network engineer must run a core Cisco Nexus 9500 Series Switch as a POAP server for all top-of-rack Cisco Nexus switches. Which two network functions must run to provide the POAP service? (Choose two.)

- A. DNS
- B. PXE
- C. BOOTP
- D. TFTP
- E. DHCP

Correct Answer: DE

---

#### QUESTION 5

A Cisco MDS Series Switch with the POAP feature boots and does not find the startup configuration. Which location is checked first when the switch enters POAP mode?

- A. USB device that contains the software image files and the switch configuration file
- B. DHCP server to bootstrap the interface IP address, gateway, DNS server, and TFTP IP addresses
- C. TFTP server where the necessary configuration files are downloaded
- D. HTTP server where the URL is used to download the software image

Correct Answer: A

[300-625 Practice Test](#)

[300-625 Study Guide](#)

[300-625 Braindumps](#)