



# 300-625<sup>Q&As</sup>

Implementing Cisco Storage Area Networking (DCSAN)

## Pass Cisco 300-625 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/300-625.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

What is the function of the 0xFFFFFC address in a Fibre Channel fabric?

- A. management server
- B. fabric controller
- C. name server
- D. time server

Correct Answer: C

### QUESTION 2

Refer to the exhibit.

#### Switch 1

```
Ivr nat
ivr vsan-topology auto
ivr service-group name GROUP1
autonomous-fabric-id 100 vsan-ranges 1-3, 100
autonomous-fabric-id 1 switch 20:00:00:05:31:11:32:ac vsan-ranges 1
autonomous-fabric-id 1 switch 20:00:00:05:40:12:1e:dd vsan-ranges 1-3
```

#### Switch 2

```
ivr vsan-topology auto
ivr service-group name GROUP2
autonomous-fabric-id 100 vsan-ranges 1, 6-7, 200
autonomous-fabric-id 1 switch 20:00:00:05:31:11:32:ac vsan-ranges 1
autonomous-fabric-id 1 switch 20:00:00:05:40:12:1e:dd vsan-ranges 6-7
```

What is the result of merging the fabric?

- A. The merged fabric IVR VSAN topology is set to activate.
- B. The merged fabric has NAT enabled.
- C. The merge is invalid.
- D. The merged fabric contains only service group Group1.

Correct Answer: D

### QUESTION 3

After a subordinate switch requests a domain ID from a principal switch, the requested domain ID becomes the runtime



domain ID, and all interfaces on the affected VSAN are isolated. What is a solution to the issue?

- A. Add the received ID to the allowed list.
- B. Configure a static domain on the subordinate switch and reboot the switch.
- C. Enable the FICON feature on the affected VSAN.
- D. Configure IVR NAT on the affected VSAN.

Correct Answer: A

#### QUESTION 4

Refer to the exhibit.

```
interface Ethernet 1/10
  priority-flow-control mode auto
```

What is the result of the configuration?

- A. No-drop CoS values are advertised by the DCBX.
- B. LFC is prioritized over PFC on Ethernet 1/10.
- C. PFC operates on Ethernet 1/10 regardless of the capability of the peer.
- D. PFC fails to operate properly unless LFC is disabled on Ethernet 1/10.

Correct Answer: A

#### QUESTION 5

Which command identifies the application and the user that have a Cisco Fabric Services session open?

- A. show cfs application
- B. show zoneset active
- C. show cfs lock D. show device-alias database

Correct Answer: A