

300-710^{Q&As}

Securing Networks with Cisco Firepower (SNCF)

Pass Cisco 300-710 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.geekcert.com/300-710.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



VCE & PDF GeekCert.com

https://www.geekcert.com/300-710.html

2024 Latest geekcert 300-710 PDF and VCE dumps Download

QUESTION 1

A hospital network needs to upgrade their Cisco FMC managed devices and needs to ensure that a disaster recovery process is in place. What must be done in order to minimize downtime on the network?

- A. Configure a second circuit to an ISP for added redundancy.
- B. Keep a copy of the current configuration to use as backup.
- C. Configure the Cisco FMCs for failover.
- D. Configure the Cisco FMC managed devices for clustering.

Correct Answer: B

https://www.cisco.com/c/en/us/td/docs/security/firepower/660/configuration/guide/fpmc-config-guide-v66/firepower_management_center_high_availability.html

Cisco Threat Intelligence Director (TID) and High Availability Configurations If you host TID on the active Firepower Management Center in a high availability configuration, the system does not synchronize TID configurations and TID data to the standby Firepower Management Center. We recommend performing regular backups of TID data on your active Firepower Management Center so that you can restore the data after failover.

QUESTION 2

An engineer has been tasked with providing disaster recovery for an organization\\'s primary Cisco FMC. What must be done on the primary and secondary Cisco FMCs to ensure that a copy of the original corporate policy is available if the primary Cisco FMC fails?

- A. Restore the primary Cisco FMC backup configuration to the secondary Cisco FMC device when the primary device fails.
- B. Connect the primary and secondary Cisco FMC devices with Category 6 cables of not more than 10 meters in length.
- C. Configure high-availability in both the primary and secondary Cisco FMCs.
- D. Place the active Cisco FMC device on the same trusted management network as the standby device.

Correct Answer: A

Reference: https://www.cisco.com/c/en/us/td/docs/security/firepower/620/configuration/guide/fpmc-config-guide-v62/firepower_management_center_high_availability.html

QUESTION 3

Administrator is attempting to remotely log into a switch in the data center using SSH and is unable to connect. How does the administrator confirm that traffic is reaching the firewall?

A. by running Wireshark on the administrator\\'s PC.



https://www.geekcert.com/300-710.html

2024 Latest geekcert 300-710 PDF and VCE dumps Download

- B. by performing a packet capture on the firewall.
- C. by running a packet tracer on the firewall.
- D. by attempting to access it from a different workstation.

Correct Answer: B

QUESTION 4

Network traffic coming from an organization\\'s CEO must never be denied. Which access control policy configuration option should be used if the deployment engineer is not permitted to create a rule to allow all traffic?

- A. Change the intrusion policy from security to balance.
- B. Configure a trust policy for the CEO.
- C. Configure firewall bypass.
- D. Create a NAT policy just for the CEO.

Correct Answer: B

QUESTION 5

An engineer must deploy a Cisco FTD appliance via Cisco FMC to span a network segment to detect malware and threats. When setting the Cisco FTD interface mode, which sequence of actions meets this requirement?

- A. Set to passive, and configure an access control policy with an intrusion policy and a file policy defined.
- B. Set to passive, and configure an access control policy with a prefilter policy defined.
- C. Set to none, and configure an access control policy with an intrusion policy and a file policy defined.
- D. Set to none, and configure an access control policy with a prefilter policy defined.

Correct Answer: A

 $Reference: https://www.cisco.com/c/en/us/td/docs/security/firepower/623/configuration/guide/fpmc-config-guide-v623/fpmc-config-guide-v623_chapter_010000001.html$

300-710 VCE Dumps

300-710 Study Guide

300-710 Braindumps