



300-715^{Q&As}

Implementing and Configuring Cisco Identity Services Engine (SISE)

Pass Cisco 300-715 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/300-715.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

In a Cisco ISE split deployment model, which load is split between the nodes?

- A. AAA
- B. network admission
- C. log collection
- D. device admission

Correct Answer: A

https://www.cisco.com/c/en/us/td/docs/security/ise/2-6/install_guide/b_ise_InstallationGuide26.pdf

QUESTION 2

In addition to the CLI, what is another option to manage a Cisco IPS?

- A. SDEE
- B. Cisco SDM
- C. Cisco IDM
- D. Cisco ISE

Correct Answer: D

QUESTION 3

The default Cisco ISE node configuration has which role or roles enabled by default?

- A. Administration only
- B. Inline Posture only
- C. Administration and Pokey Service
- D. Policy Service Monitoring, and Administration

Correct Answer: D

QUESTION 4

What happen when an internal user is configured with an external identity store for authentication but an engineer uses the cisco ise admin portal to select an internal identity store as the identity source?



- A. Authentication is granted
- B. Authentication failed
- C. Authentication is redirected to an external identity store
- D. Authentication is redirected to an external identity store

Correct Answer: B

QUESTION 5

An administrator is configuring a switch port for use with 802.1X.

What must be done so that the port will allow voice and multiple data endpoints?

- A. Connect a hub to the switch port to allow multiple devices access after authentication.
- B. Configure the port with the authentication host-mode multi-auth command.
- C. Connect the data devices to the port, then attach the phone behind them.
- D. Use the command authentication host-mode multi-domain on the port.

Correct Answer: B

Reference: <https://networklessons.com/cisco/ccie-routing-switching-written/mac-authentication-bypass-mab>

[300-715 PDF Dumps](#)

[300-715 VCE Dumps](#)

[300-715 Exam Questions](#)