



300-735^{Q&As}

Automating and Programming Cisco Security Solutions (SAUTO)

Pass Cisco 300-735 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/300-735.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A developer has just completed the configuration of an API that connects sensitive internal systems. Based on company policies, the security of the data is a high priority.

Which approach must be taken to secure API keys and passwords?

- A. Embed them directly in the code.
- B. Store them in a hidden file.
- C. Store them inside the source tree of the application.
- D. Change them periodically.

Correct Answer: D

QUESTION 2

Which two methods are API security best practices? (Choose two.)

- A. Use tokens after the identity of a client has been established.
- B. Use the same operating system throughout the infrastructure.
- C. Use encryption and signatures to secure data.
- D. Use basic auth credentials over all internal API interactions.
- E. Use cloud hosting services to manage security configuration.

Correct Answer: AC

QUESTION 3

Refer to the exhibit.

```
quiz = [  
  {  
    "question": "Which of these is an IEEE standard for port-based Network Access Control",  
    "choices": {"a": "802.11x", "b": "802.1x", "c": "802.11a", "d": "802.11b"},  
    "answer": "b"  
  },  
]
```

Which expression prints the text "802.1x"?



- A. `print(quiz[0][\\choices\\][\\b\\])`
- B. `print(quiz[\\choices\\][\\b\\])`
- C. `print(quiz[0][\\choices\\][\\b\\][\\802.1x\\])`
- D. `print(quiz[0][\\question\\][\\choices\\][\\b\\])`

Correct Answer: A

QUESTION 4

DRAG DROP

Drag and drop the code to complete the Cisco Umbrella Investigate WHOIS query that returns a list of domains that are associated with the email address "admin@example.com". Not all options are used.

Select and Place:

<code>"https://investigate.api.umbrella.com/</code>				<code>/</code>
	<code>/</code>		<code>"</code>	
email	emails	WHOIS		
admin@example.com	whois	{admin@example.com}		

Correct Answer:

<code>"https://investigate.api.umbrella.com/</code>			WHOIS	<code>/</code>
emails	<code>/</code>	admin@example.com	<code>"</code>	
email				
	whois	{admin@example.com}		

Explanation: <https://docs.umbrella.com/investigate-api/docs/whois-information-for-a-domain-1>

QUESTION 5

If the goal is to create an access policy with the default action of blocking traffic, using Cisco Firepower Management Center REST APIs, which snippet is used?



- A. - API PATH:
`/api/fmc_config/v1/domain/<domain_uuid>/object/accesspolicies`
- METHOD:
POST
- INPUT JSON:
- ```
{
 "type": "AccessPolicy",
 "name": "AccessPolicy-test-1",
 "defaultAction": {
 "action": "BLOCK"
 }
}
```
- B. - API PATH:  
`/api/fmc_config/v1/domain/<domain_uuid>/object/securityzones`
- METHOD:  
POST
- INPUT JSON:
- ```
{  
  "type": "AccessPolicy",  
  "name": "AccessPolicy-test-1",  
  "defaultAction": {  
    "action": "BLOCK"  
  }  
}
```
- C. - API PATH:
`/api/fmc_config/v1/domain/<domain_uuid>/object/accesspolicies`
- METHOD:
PUT
- INPUT JSON:
- ```
{
 "type": "AccessPolicy",
 "name": "AccessPolicy-test-1",
 "defaultAction": {
 "action": "BLOCK"
 }
}
```



D.

- API PATH:  
`/api/fmc_config/v1/domain/<domain_uid>/object/accesspolicies`
- METHOD:  
POST
- INPUT JSON:  
{  
 "type": "AccessPolicy",  
 "name": "AccessPolicy-test-1",  
 "action": "FASTPATH"  
}

A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: D

[Latest 300-735 Dumps](#)

[300-735 Study Guide](#)

[300-735 Braindumps](#)