



# 3100<sup>Q&As</sup>

Avaya Aura Contact Recording and Avaya Aura Quality Monitoring  
Implementation Exam

## Pass Avaya 3100 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/3100.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

Which setting in the system parameter feature screen will enable TTI to be applicable to both analog and digital stations?

- A. Terminal Trans. Init.? Y, TTI state = `voice\\`, TTI enable = `y\\`, TTI security code = `1709\\`, CTI enabled = `n\\`.
- B. Terminal Trans. Init.? Y, TTI state = `data\\`, TTI enable = `y\\`, TTI security code = `1709\\`, CTI enabled = `y\\`.
- C. Terminal Trans. Init.? Y, TTI state = `vdata\\`, TTI enable = `y\\`, TTI security code = `1709\\`, CTI enabled = `n\\`.
- D. Terminal Trans. Init.? Y, TTI state = `voice\\`, TTI enable = `y\\`, TTI security code = `1709\\`, CTI enabled = `y\\`.

Correct Answer: D

---

### QUESTION 2

Which component registers SIP Endpoints?

- A. System Manager
- B. Communication Manager
- C. Switch
- D. Session Manager

Correct Answer: D

Reference:<https://downloads.avaya.com/css/P8/documents/100082635>(page 15, communication manager evolution server)

---

### QUESTION 3

You want a user's station to be able to dial extension 5605 and 5608 only.

Which station configuration will achieve this?

- A. Assign COR 11 to user's station, In COR11 Set COR-to COR calling permission = `n\\` for all except COR 10. Assign COR to 5605 and 5608. Ensure that these two CORs are not assigned to any other station object.
- B. The FRL = 7 to user's station. FRL = 7 to station 5606 and 5608. Set FRL for all other stations to 6 and lesser
- C. Assign COR 10 to user's station. In COR 11, set CPR-to-COR calling permission = `n\\` for all except. Assign COR 11 to 5605 and 5608. Ensure that these two CORs are not assigned to any other object.
- D. The FRL = 5 to user's station, FRL = 7 to station 5606 and 5608. Set FRL for all other stations to 5 or lesser.

Correct Answer: A

---



#### QUESTION 4

All release 0x and later Avaya Aura® Communication Manager (CM) deployments support secure link access: SAL for remote access to the server and alarm notification from the server to the support engineer?

Which hardware or software is required at the customer site for SAL support of the CM server?

- A. SAL software is required and uses a separate SAL server.
- B. SAL software is required and uses a secure external modem.
- C. SAL software is part of System Platform and requires no additional hardware.
- D. SAL software is part of System Platform and uses a remote maintenance board (RMB) that must be installed in the server.

Correct Answer: C

---

#### QUESTION 5

The monitor and display capacity commands can be used to get a real-time status of the system using Avaya Site Administration (ASA). Which command and tool should you use to view a summary of the overall condition of the system?

- A. Monitor system command using terminal emulationmode
- B. Monitor system command using GEDI
- C. Monitor status command using terminal emulationmode
- D. Display status using GEPI or terminal emulationmode

Correct Answer: A

[3100 PDF Dumps](#)

[3100 VCE Dumps](#)

[3100 Practice Test](#)