



350-801^{Q&As}

Implementing and Operating Cisco Collaboration Core Technologies
(CLCOR)

Pass Cisco 350-801 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/350-801.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which task is required when configuring self-provisioning for an end user in Cisco UCM?

- A. Enable Auto-Registration.
- B. Associate the end user to the Standard CCM Super Users group.
- C. Associate the end user to a SIP Profile.
- D. Disable Auto-Registration.

Correct Answer: A

This auto registration must be enabled for the self-provisioning to work due to needing the phone able to register to CUCM first.

Reference:

<https://www.cisco.com/c/en/us/support/docs/unified-communications/unified-communications-manager-callmanager/214233-configure-self-provisioning-feature-on-c.html>

QUESTION 2

Which external DNS SRV record must be present for Mobile and Remote Access?

- A. _cisco-uds._tcp.example.com
- B. _collab-edge._tls.example.com
- C. _collab-edge._tcp.example.com
- D. _cisco-uds._tls example.com

Correct Answer: B

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/expressway/config_guide/X14-0-1/mra/exwy_b_mra-deployment-guide-x1401/exwy_m_requirements-for-mra.html

QUESTION 3

An administrator configures international calling on a Cisco UCM cluster and wants to minimize the number of route patterns that are needed. Which route pattern enables the administrator to match variable-length numbers?

- A. 9.011@
- B. 9.011#
- C. 9.011*
- D. 9.011!



Correct Answer: D

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/srnd/collab12/collab12/dialplan.html

QUESTION 4

Which configuration on Cisco Unified Communications Manager is required for SIP MWI to work?

- A. The line partition must be inside the inbound CSS assigned to the CUC SIP trunk.
- B. The line partition must be inside the rerouting CSS assigned to the Cisco Unity Connection SIP trunk.
- C. Set the "Enable message waiting indicator" on the part group.
- D. Assign a MWI extension on the mailbox.

Correct Answer: A

The line partition must be inside the inbound CSS assigned to the CUC SIP trunk. This ensures that the SIP MWI messages are sent to the correct destination.

The other options are incorrect because:

Assigning an MWI extension on the mailbox is not required for SIP MWI to work. The line partition does not need to be inside the rerouting CSS assigned to the Cisco Unity Connection SIP trunk.

Setting the "Enable message waiting indicator" on the port group is not required for SIP MWI to work.

QUESTION 5

What are two key features of the Expressway series? (Choose two.)

- A. VPN connect toward the internal UC resources
- B. B2B calls
- C. IP to PSTN call connectivity
- D. Device registration over the internet
- E. SIP header modification

Correct Answer: BD

Registration directly to Expressway. This option is new in Expressway X8.9. Registering users and devices directly to Expressway (both SIP and H.323 registrations are supported with Expressway-C, and proxy SIP registration is supported with Expressway-E) enables you to extend video-centric services to users. and Feature is ofc b2b