



# 350-801<sup>Q&As</sup>

Implementing and Operating Cisco Collaboration Core Technologies  
(CLCOR)

**Pass Cisco 350-801 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/350-801.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

Which four requirements are mandatory to enable a mixed mode Cisco Unified CM cluster? (Choose four.)

- A. Cisco CTL Provider Service activated and enabled
- B. Cisco Certificate Authority Proxy Function activated and enabled
- C. Cisco Trust Verification activated and enabled
- D. Cisco CTL client
- E. a minimum of one USB e-token
- F. a minimum of two USB e-token
- G. a minimum of one soft e-token

Correct Answer: ABDF

---

### QUESTION 2

What are the predefined call handlers in Cisco Unity Connection?

- A. opening greeting, operator, and goodbye
- B. opening greeting, welcome, and default system
- C. greetings, operator, and closed
- D. caller input, greetings, and transfer

Correct Answer: A

Reference: [https://www.cisco.com/en/US/docs/voice\\_ip\\_comm/connection/1x/administration/guide/acm030.html](https://www.cisco.com/en/US/docs/voice_ip_comm/connection/1x/administration/guide/acm030.html)

---

### QUESTION 3

Refer to the exhibit.



**Pattern Definition**

Route Pattern*	\+011!
Route Partition	International_PT
Description	Globalized Routing
Numbering Plan	-- Not Selected --
Route Filter	< None >
MLPP Precedence*	Default
<input type="checkbox"/> Apply Call Blocking Percentage	
Resource Priority Namespace Network Domain	< None >
Route Class*	Default
Gateway/Route List*	PSTN_RL

**-Pattern Definition**

Route Pattern*	011.!
Route Partition	International_PT
Description	Globalized Routing
Numbering Plan	-- Not Selected --
Route Filter	< None >
MLPP Precedence*	Default
<input type="checkbox"/> Apply Call Blocking Percentage	
Resource Priority Namespace Network Domain	< None >
Route Class*	Default
Gateway/Route List*	PSTN_RL

**-Pattern Definition**

Route Pattern*	\+1.!
Route Partition	International_PT
Description	Globalized Routing
Numbering Plan	-- Not Selected --
Route Filter	< None >
MLPP Precedence*	Default
<input type="checkbox"/> Apply Call Blocking Percentage	
Resource Priority Namespace Network Domain	< None >
Route Class*	Default
Gateway/Route List*	PSTN_RL

An engineer is troubleshooting why PSTN phones are not receiving the caller's name when called from a remote Cisco UCM site. An ISDN PRI connection is being used to reach the PSTN. What must the administrator select to resolve the issue?

- A. isdn send display ie
- B. isdn enable clid
- C. isdn outgoing display-ie
- D. isdn supp-service name calling

Correct Answer: D

Reference: [https://www.cisco.com/c/en/us/td/docs/ios/voice/command/reference/vr\\_book/vr\\_i2.html](https://www.cisco.com/c/en/us/td/docs/ios/voice/command/reference/vr_book/vr_i2.html)



#### QUESTION 4

As a voice engineer, which two recommendations do you to make to your company to optimize Cisco Unified Communications Manager configuration to reduce the number of toll fraud incidents? (Choose two.)

- A. Classify all route patterns as on-net and prohibit on-net to on-net call transfers in Cisco Unified CM service parameters.
- B. Classify all route patterns as off-net and prohibit off-net to off-net call transfers in Cisco Unified CM service parameters.
- C. Classify all route patterns as on-net or off-net and prohibit off-net to off-net call transfers in Cisco Unified CM service parameters.
- D. Inbound CSS on any gateway typically should have access to internal destinations and PSTN destinations.
- E. Inbound CSS on any gateway typically should have access to internal destinations only and not PSTN destinations.

Correct Answer: CE

---

#### QUESTION 5

An engineer is deploying Webex app on Microsoft Windows computers. The engineer wants to ensure that the end users do not receive pop-IQ dialogues

When they start the application Much two actions ensure the end users are not prompted to accept the end-user license (Choose two )

- A. Set the DELETEUSERDATA=r installation argument
- B. Set the "HKEY\_LOCAL\_MACHINE,.Software