



352-001^{Q&As}

CCDE Written Exam

Pass Cisco 352-001 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/352-001.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

You are redesigning a high-speed transit network due to congestion-related issues. Which congestion avoidance mechanism can you apply to the existing network?

- A. NBAR
- B. FIFO
- C. WRED
- D. Rate-limit
- E. Policy-Based Routing

Correct Answer: C

QUESTION 2

Which statement about OSPF incremental SPF is true?

- A. iSPF must be enabled on all routers in the domain.
- B. iSPF must be enabled on all routers in a particular area.
- C. iSPF capability is advertised using Opaque LSAs.
- D. iSPF is local to the router and does not require interoperability.
- E. iSPF is negotiated during the OSPF adjacency process.

Correct Answer: D

QUESTION 3

Two MPLS service providers (SP1 and SP2) are offering inter-provider RFC 2547/4364- based IP-VPN service to an enterprise customer. IP traffic among some of the customer's sites has to traverse both of the service providers. The service providers and the enterprise do not know what the minimum MTU is along the end-to-end path.

What could be done to guarantee that large packets are not dropped for MTU-related reasons?

- A. enable Path MTU Discovery on all devices within SP1 and SP2
- B. enable Path MTU Discovery on all devices within the enterprise
- C. configure the IP sender or senders to set the DF flag in the IP header
- D. configure the IP sender or senders to clear the DF flag in the IP header



Correct Answer: B

QUESTION 4

In an MPLS-VPN environment, what is the effect of configuring an identical set of route targets for a particular VRF, but then configuring nonidentical route distinguisher across multiple PE devices?

- A. The routes will be correctly handled by the control plane, but there will be instances where routes take up twice as much memory.
- B. The routes will propagate to the remote PE, but the PE will never install them in its forwarding table.
- C. The routes will be rejected by the remote PE because they have a different RD than its routes.
- D. The routes will not even be sent to any remote PE with a different RD.

Correct Answer: A

QUESTION 5

Which three of the following security controls would you take into consideration when implementing IoT capabilities?

- A. Layered security approach
- B. Place security above functionality
- C. Define lifecycle controls for IoT devices
- D. Privacy impact Assessment
- E. Change passwords every 90 days
- F. Implement intrusion detection systems on IoT Devices

Correct Answer: ACD

[Latest 352-001 Dumps](#)

[352-001 Study Guide](#)

[352-001 Braindumps](#)