



3605^{Q&As}

Avaya Ethernet Routing Switch Implementation and Maintenance Exam

Pass Avaya 3605 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/3605.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which statement describes how to configure Simple Loop Prevention protocol (SLPP) Rx?

- A. SLPP is configured on the edge switch ports that connect to the core switch cluster.
- B. SLPP is configured on the core switch cluster ports that connect to the edge switch.
- C. SLPP is configured on the Inter Switch Trunk (1ST) ports of the core switch cluster.
- D. SLPP is configured on the uplink ports of both the core switch cluster and the edge switch

Correct Answer: D

QUESTION 2

A technician is configuring password levels on the Ethernet Routing Switch (ERS) 8600, and wants the manager to be able to view and edit device settings, but not to be able to change security and password settings. Which Login Level should be set for the manager?

- A. Layer 2 Read-Write Accesses
- B. Layer 3 Read-Write Access
- C. Read-Write-All Access
- D. Read-Write Access

Correct Answer: D

QUESTION 3

In Ethernet Routing Switch (ERS) 5600 switch was added into the existing ERS 5500 stack, but it did not form a proper stack. Which statement describes the problem?

- A. The ERS 5600 was set as the Base Unit.
- B. The stack was reset for a change in Base Unit to take effect.
- C. The mode parameter on the ERS 5600 switch was set to Mixed Mode.
- D. The ERS 5500 was set as the Base Unit.

Correct Answer: D

QUESTION 4

The exhibit indicates the two show commands from an edge Ethernet Routing Switch (ERS) 5520-24T- PWR an untagged frame arrives on port 10, which is configured as an access port. To which VLAN will the packet be forwarded?



```
5520 Edge (SSH)
5520-24T-PUR#show vlan int info 10-11
  Filter      Filter
  Untagged    Unregistered
Port  Frames   Frames   PVID PRI   Tagging   Name
-----
10   No        Yes      312  0   TagAll    Port 10
11   No        Yes      312  0   TagAll    Port 11
5520-24T-PUR#show vlan int vid 10-11
Port VLAN VLAN Name   VLAN VLAN Name   VLAN VLAN Name
-----
10   311  VLAN-311    312  VLAN-312
11   311  VLAN-311    312  VLAN-312
5520-24T-PUR#
```

- A. All untagged packets will be placed in the default VLAN (VLAN 1).
- B. All untagged packets will be discarded.
- C. All untagged packets will be placed in VLAN 311
- D. All untagged packets will be placed in VLAN 31?

Correct Answer: B

QUESTION 5

Which feature should be configured to limit which ports receive multicast streams?

- A. igmp proxy
- B. igmp pruning
- C. igmp snooping
- D. PIM-SM snooping

Correct Answer: C

[3605 PDF Dumps](#)

[3605 Study Guide](#)

[3605 Braindumps](#)