



3V0-21.21^{Q&As}

Advanced Design VMware vSphere 7.x

Pass VMware 3V0-21.21 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/3v0-21-21.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

An architect is designing a vSphere environment for a customer based on the following information:

The vSphere cluster will have three hosts only due to budget considerations.

A database cluster (node majority) consisting of three virtual machines will be running on the vSphere cluster.

Which two recommendations can the architect make so that the customer achieves the highest level of application availability while taking into consideration operational resiliency? (Choose two.)

- A. Create VM-VM anti-affinity rules
- B. Set das.respectvmvmantiaffinityrules to false
- C. Create VM-Host anti-affinity rules
- D. Disable vSphere HA during maintenance
- E. Set das.ignoreinsufficienthbdatabase to true

Correct Answer: BC

QUESTION 2

An architect is designing a new vSphere environment to meet the following requirements:

The environment must support 5,000 virtual machines.

The environment will be built initially using 350 hosts.

Which vCenter Server appliance deployment size should the architect specify for the design?

- A. Large
- B. Small
- C. Tiny
- D. Medium

Correct Answer: A

QUESTION 3

During a requirements gathering workshop, the customer provides the following requirement:



A new vSphere platform must be designed securely and all interfaces must be protected against potential snooping.

How should this non-functional security requirement be documented?

- A. Interfaces must be audited.
- B. Encrypted channels must be used for all communications.
- C. Unauthorized access to interfaces must be reported within 15 minutes.
- D. Communications must be through Private VLANs (PVLAN).

Correct Answer: A

QUESTION 4

An architect is tasked with designing a greenfield VMware software-defined data center (SDDC) solution that will be used to deliver a private cloud service for a customer.

During the initial meeting with the service owner and business sponsor, the customer has provided the following information to help inform the design:

The solution must initially support the concurrent running of 300 production and 600 development virtual machines.

The production environment should be delivered across two geographically dispersed data centers.

The development environment must be vSphere-based but does not have to be deployed on-premises.

The two data centers are connected to each other through multiple diversely routed, high bandwidth and low latency links.

The customer's server hardware standard document states that all virtual infrastructure hosts must be based on blade architecture only.

The service owner has said that is important to ensure that neither the availability target of 99.5% nor the resource capacity is affected when the operations team completes maintenance activities, such as the monthly software patching and ad-hoc hardware break/fix.

All virtual machine backups must be completed using the existing backup service.

The recovery time objective (RTO) for the service is four hours.

The recovery point objective (RPO) of the service is 24 hours.



Given the information from the customer, which two would be classified as assumptions within the design? (Choose two.)

- A. The backup service will store data in a secure facility
- B. The backup service has sufficient capacity for the new requirements
- C. The customer will update their hardware standard to support rack mount servers
- D. All virtual machines will be deployed with the same resource profile for production and development
- E. The clusters will have a minimum redundancy of N+1

Correct Answer: AC

QUESTION 5

An architect is designing a vSphere environment for a customer and learns that the customer has:

A single vSphere cluster Two storage arrays with different RAID capabilities

Which two design decisions should the architect make to maximize data availability and data performance for this customer? (Choose two.)

- A. Use Storage DRS.
- B. Use VMDK anti-affinity rules.
- C. Use multiple datastores for heartbeat.
- D. Use a minimum of three storage arrays.
- E. Use VM to host DRS rules.

Correct Answer: AC

[Latest 3V0-21.21 Dumps](#)

[3V0-21.21 Study Guide](#)

[3V0-21.21 Braindumps](#)