



3V0-42.20^{Q&As}

Advanced Design VMware NSX-T Data Center

Pass VMware 3V0-42.20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/3v0-42-20.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

An architect is helping an organization with the Physical Design of an NSX-T Data Center solution.

This information was gathered during a workshop:

The company will use a Leaf and Spine physical network architecture with Layer 3 gateways for top of rack switches.

The company is planning to deploy 120 ESX hosts across 10 racks.

There will be a total of a 12 clusters where each cluster has one host per rack.

What should the architect recommend to allow applications to run on any host in the cluster? (Choose the best answer.)

- A. Deploy all application networks on NSX segments.
- B. Deploy an L2 VPN to allow the networks to extend to each host.
- C. Deploy a Tier-0 gateway per Rack and configure BGP between racks.
- D. Deploy a Tier-1 gateway per Rack and configure BGP between racks.

Correct Answer: D

QUESTION 2

An architect is helping an organization with the Logical Design of an NSX-T Data Center solution.

During discussions about centralized services NAT running on Tier-1 or Tier-0 Gateway, the customer made these requests:

Services contain stateful services.

Services should be in high availability mode.

Which two selections should the architect include in their design? (Choose two.)

- A. An active/active model should be used.
- B. Use Reflexive NAT on the uplink interface.
- C. DNAT should be applied on the uplink interface.
- D. Mix stateful and stateless NAT rules on the same gateway.
- E. The high availability mode supported is only Active-Standby.



Correct Answer: DE

QUESTION 3

An architect is designing a solution for containerization. The solution will include high availability and security using NSX-T Data Center. The architect plans to provide a basic required components list in the Logical Design.

Which solution should the architect recommend? (Choose the best answer.)

- A. 3 NSX Managers, 3 virtual NSX Edges, two Tier-0 gateways in Active/Standby, BGP configuration
- B. 2 NSX Managers, 2 virtual NSX Edges, one Tier-0 gateway, BGP configuration and a static route
- C. 3 NSX Managers, 3 virtual NSX Edges, one Tier-0 gateway and a static route and OSPF
- D. 1 NSX Manager, 2 virtual NSX Edges, two Tier-0 gateways in Active/Active, BGP configuration

Correct Answer: A

QUESTION 4

Which three choices are part of a Design Approach when discussing design alternatives and their effects? (Choose three.)

- A. backup
- B. budget
- C. cost
- D. performance
- E. knowledge
- F. security

Correct Answer: DEF

QUESTION 5

According to the Discover Task of the Engagement Lifecycle, which statement would be classified as a risk? (Choose the best answer.)

- A. Enough power and cooling capacity is available in each rack in the data center.
- B. To retain certification to provide financial services to end customers, PCI-DSS audits need to be passed.
- C. A merger and acquisition process was recently completed and new company on-boarding is not completed.



D. Due to existing contracts and purchase agreements, the existing server hardware needs to be reused.

Correct Answer: B

[Latest 3V0-42.20 Dumps](#)

[3V0-42.20 VCE Dumps](#)

[3V0-42.20 Practice Test](#)