



# 3V0-42.20<sup>Q&As</sup>

Advanced Design VMware NSX-T Data Center

**Pass VMware 3V0-42.20 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/3v0-42-20.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by VMware  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

An architect is helping an organization with the Logical Design of an NSX-T Data Center solution.

This information was gathered during the Assessment Phase:

Customer currently has a single 10 host vSphere cluster.

Customer wants to improve network security and automation.

Current cluster utilization and business policies prevent changing the existing vSphere deployment.

High-availability is important to the customer.

Which three selections should the architect include in their design? (Choose three.)

- A. Apply vSphere DRS VM-Host anti-affinity rules to the virtual machines of the NSX-T Edge cluster.
- B. Deploy at least two NSX-T Edge virtual machines in the vSphere cluster.
- C. Deploy the NSX Controllers in the management cluster.
- D. Apply vSphere Distributed Resource Scheduler (vSphere DRS) VM-Host anti-affinity rules to NSX Managers.
- E. Remove 2 hosts from the cluster and create a new edge cluster.
- F. Remove vSphere DRS VM-Host affinity rules to the NSX-T Controller VMs.

Correct Answer: ACE

---

### QUESTION 2

An architect is helping an organization with the Logical Design of a Layer 2 bridging solution.

This information was gathered during the Assessment Phase:

Workloads are running on ESXi hosts.

Workloads are running on KVM hosts.

Workloads on hypervisors should use bridging services.

VLAN 50 is used for Tier-0 uplink connectivity.

Which selection should the architect include in their design? (Choose the best answer.)

- A. Create an NSX Edge Bridge Cluster and configure the bridging profile with VLAN 60.
- B. Create an NSX Edge Bridge Cluster and configure the bridging profile with VLAN 50.
- C. Create an ESXi Bridge Cluster and configure the bridging profile with VLAN 50.



D. Create an ESXi Bridge Cluster and configure the bridging profile with VLAN 60.

Correct Answer: B

---

### QUESTION 3

An architect is helping an organization with the Conceptual Design of an NSX-T Data Center solution.

Which risk is documented by an architect? (Choose the best answer.)

- A. The security team has a firewall communication matrix documented.
- B. The team is not trained for NSX-T but have a very strong experience with vSphere.
- C. Open communication between different application tiers is not allowed.
- D. Aggregate N-S throughput at any given time should be at least 10G.

Correct Answer: B

---

### QUESTION 4

Which three assessment findings are part of a Conceptual Design? (Choose three.)

- A. risks
- B. host names
- C. justifications
- D. constraints
- E. assumptions
- F. vendor model

Correct Answer: ACD

---

### QUESTION 5

Which is a family of solutions for data center designs that span compute, storage, networking, and management, serving as a blueprint for a customer's Software Defined Data Center (SDDC) implementations? (Choose the best answer.)

- A. VMware SDDC Design
- B. VMware Validated Design
- C. VMware POC Design



D. VMware Cloud Foundation

Correct Answer: B

[Latest 3V0-42.20 Dumps](#)

[3V0-42.20 VCE Dumps](#)

[3V0-42.20 Exam Questions](#)