



3V0-42.20^{Q&As}

Advanced Design VMware NSX-T Data Center

Pass VMware 3V0-42.20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/3v0-42-20.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

An architect is helping an organization with the Conceptual Design of an NSX-T Data Center solution. This information was gathered by the architect during the Discover Task of the Engagement Lifecycle:

There are applications which use IPv6 addressing.

Network administrators are not familiar with NSX-T Data Center solutions.

Hosts can only be configured with two physical NICs.

There is an existing management cluster to deploy the NSX-T components.

Dynamic routing should be configured between the physical and virtual network.

There is a storage array available to deploy NSX-T components.

Which two requirements were documented by the architect? (Choose two.)

- A. There are applications which use IPv6 addressing.
- B. Dynamic routing should be configured between the physical and virtual network.
- C. Hosts can only be configured with two physical NICs.
- D. The storage array has enough capacity to deploy NSX components.
- E. Network administrators are not familiar with NSX-T Data Center solutions.

Correct Answer: BD

QUESTION 2

A Solutions Architect is designing an environment with 1,200 services being offered through the NSX-T Data Center Load Balancer.

Which three selections are necessary to meet the minimum requirements to support the solution? (Choose three.)

- A. Extra Large Load Balancer
- B. Tier 1 Gateway
- C. Tier 0 Gateway
- D. Large Edge Node
- E. Extra Large Edge Node
- F. Large Load Balancer

Correct Answer: BDF



QUESTION 3

An architect is helping an organization with the Physical Design of an NSX-T Data Center solution.

This information was gathered during a workshop:

Current hypervisor of choice is KVM.

Cost reduction is important.

Which two selections should the architect recommend to the organization? (Choose two.)

- A. Deploy Edge VM Nodes using ISO.
- B. Deploy NSX Manager using OVF.
- C. Deploy NSX Manager using QCOW2.
- D. Deploy bare metal Edge Nodes.
- E. Deploy Edge VM Nodes on KVM.

Correct Answer: CD

QUESTION 4

An architect is helping an organization with the Physical Design of an NSX-T Data Center solution.

This information was gathered during a workshop:

The company will use a Leaf and Spine physical network architecture with Layer 3 gateways for top of rack switches.

The company is planning to deploy 120 ESX hosts across 10 racks.

There will be a total of 12 clusters where each cluster has one host per rack.

What should the architect recommend to allow applications to run on any host in the cluster? (Choose the best answer.)

- A. Deploy all application networks on NSX segments.
- B. Deploy an L2 VPN to allow the networks to extend to each host.
- C. Deploy a Tier-0 gateway per Rack and configure BGP between racks.
- D. Deploy a Tier-1 gateway per Rack and configure BGP between racks.

Correct Answer: D



QUESTION 5

Which three assessment findings are part of a Conceptual Design? (Choose three.)

- A. risks
- B. host names
- C. justifications
- D. constraints
- E. assumptions
- F. vendor model

Correct Answer: ACD

[3V0-42.20 VCE Dumps](#)

[3V0-42.20 Exam Questions](#)

[3V0-42.20 Braindumps](#)