



400-007^{Q&As}

Cisco Certified Design Expert (CCDE Written)

Pass Cisco 400-007 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/400-007.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

What are two primary design constraints when a robust infrastructure solution is created? (Choose two.)

- A. monitoring capabilities
- B. project time frame
- C. staff experience
- D. component availability
- E. total cost

Correct Answer: DE

Component availability: Availability of required components and technologies is a critical factor in designing a robust infrastructure solution.

QUESTION 2

A security architect receives reports of these incidents:

1.

An attacker exploits printers and medical devices in the organization to gain control of the network.

2.

An attacker disrupts operations through attacks on networked business infrastructure. What is the next step to address these issues after discovery and classification of devices?

- A. Ensure trustworthiness of devices
- B. Assess continuous security health monitoring
- C. Apply a context-based network access control policy
- D. Enforce risk-based and adaptive access policies

Correct Answer: C

<https://www.ciscolive.com/c/dam/r/ciscolive/emea/docs/2020/pdf/ADD-1001-Zero-Trust-Security-Model.pdf> (Zero Trust for workplace)

QUESTION 3

DRAG DROP

Drag and drop the design characteristics from the left onto the correct network filter techniques on the right. Not all options are used.



Select and Place:

It is used to prevent spoofing attacks when there are alternate routes to a given IP address

It is used to check the existence of a route without regard to the incoming interface

It is a dynamic filter

It requires manual configuration

It is used as a filtering technique for Martian IP addresses

Ingress Access Lists

target 1

Strict Reverse Path Forwarding

target 2

Feasible Path Reverse Path Forwarding

target 3

Loose Reverse Path Forwarding

target 4

Correct Answer:

It is used to check the existence of a route without regard to the incoming interface

Ingress Access Lists

It requires manual configuration

Strict Reverse Path Forwarding

It is a dynamic filter

Feasible Path Reverse Path Forwarding

It is used to prevent spoofing attacks when there are alternate routes to a given IP address

Loose Reverse Path Forwarding

It is used as a filtering technique for Martian IP addresses

QUESTION 4

The General Bank of Greece plans to upgrade its legacy end-of-life WAN network with a new flexible, manageable, and scalable solution. The main requirements are ZTP support, end-to-end encryption application awareness and segmentation. The CTO states that the main goal of the bank is CAPEX reduction. Which WAN technology should be used for the solution?

A. SD-branch



- B. DMVPN with PfR
- C. managed SD-WAN
- D. SD-WAN

Correct Answer: C

QUESTION 5

When designing a WAN that will be carrying real-time traffic, what are two important reasons to consider serialization delay? (Choose two)

- A. Serialization delays are invariable because they depend only on the line rate of the interface
- B. Serialization delays are variable because they depend on the line rate of the interface and on the type of the packet being serialized.
- C. Serialization delay is the time required to transmit the packet on the physical media.
- D. Serialization delays are variable because they depend only on the size of the packet being serialized
- E. Serialization delay depends not only on the line rate of the interface but also on the size of the packet

Correct Answer: BD

[400-007 PDF Dumps](#)

[400-007 Study Guide](#)

[400-007 Braindumps](#)