

400-101^{Q&As}

CCIE Routing and Switching Written

Pass Cisco 400-101 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.geekcert.com/400-101.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



https://www.geekcert.com/400-101.html

2021 Latest geekcert 400-101 PDF and VCE dumps Download

QUESTION 1

Which three criteria are used for stackwise election of a master switch?

- A. VLAN revision number
- B. longest uptime
- C. highest MAC address
- D. user-selected priority
- E. IOS version number
- F. lowest MAC address

Correct Answer: BDF

QUESTION 2

Which two statements about a flat single-hub DMVPN with NHRP are true? (Choose two)

- A. NHRP shortens the configuration 01the hub router
- B. NHRP dynamically provides information about the spoke routers to the hub
- C. NHRP disables multicast
- D. The hub muter uses NHRP to initiate the GRE tunnel with spokes
- E. The spoke routers act as the NHRP servers

Correct Answer: AB

QUESTION 3

Refer to the exhibit. Which two possible reasons why the administrator is unable to log into the switch remotely are true? (Choose two.)

GeekCert.com

https://www.geekcert.com/400-101.html

2021 Latest geekcert 400-101 PDF and VCE dumps Download

```
Rl# show run
ip domain name cisco.com
username Cisco secret 4 tnhtc92DXBhelxjYk8LWJrPV36S2i4ntXrpb4RFmfqY
interface LoopbackO
   ip address 10.10.99.1 255.255.255.0
interface Ethernet0/0
   ip address 10.10.1.1 255.255.255.0
line con 0
   exec-timeout 0 0
   privilege level 15
   logging synchronous
line aux 0
line vty 0 2
   logging synchronous
   login local
   transport input telnet ssh
line vty 3 4
   logging synchronous
   login local
   transport input ssh
Rl#show line
             Tx/Rx
      Typ
                            Modem
                                   Roty Acc0 AccI
                                                      Uses Noise Overruns
Tty
                                                                             Int
      O CTY
                                                      0
                                                            0
                                                                   0/0
      1 AUX 9600/9600
                                                            0
                                                                   0/0
                                                      O
      2 VTY
                                                      1
                                                            0
                                                                   0/0
      3 VTY
                                                      1
                                                            0
                                                                   0/0
                                                      1
                                                            0
      4 VTY
                                                                   0/0
      5 VTY
                                                      1
                                                            0
                                                                   0/0
                                                      0
      & VTY
                                                                   0/0
PC1#ssh -1 Cisco 10.10.1.1
* Connection refused by remote host
PC1#telnet 10.10.1.1
Trying 10.10.1.1 ...
* Connection refused by remote host
```

- A. An ACL is configured to reject connections from PC1
- B. The user is using the incorrect username
- C. SSH is disabled
- D. The baud rate is misconfigured
- E. The Telnet VTY lines are busy

Correct Answer: CE

https://www.geekcert.com/400-101.html

2021 Latest geekcert 400-101 PDF and VCE dumps Download

QUESTION 4

Select and Place:

Forms a half-mesh topology through peers configured with the "unicast-listen" keyword.

The default EIGRP peering method.

Use the "neighbor" statement on a nonpassive interface with default options,

Use the "remote" keyword in the neighbor statement to from peerings.

M	uľ	tic	as	ĺ

OTP point-to-point

OTP route-reflector

Unicast

Correct Answer:

The default EIGRP peering method.

Use the "remote" keyword in the neighbor statement to from peerings.

Forms a half-mesh topology through peers configured with the "unicast-listen" keyword.

Use the "neighbor" statement on a nonpassive interface with default options.

QUESTION 5

In a DMVPN solution, which component can the GRE tunnel source and destination generate automatically?

- A. pre-shared keys
- B. crypto ACLs
- C. QoS markings
- D. policy maps

Correct Answer: B

400-101 VCE Dumps

400-101 Practice Test

400-101 Study Guide

https://www.geekcert.com/400-101.html

2021 Latest geekcert 400-101 PDF and VCE dumps Download

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.geekcert.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © geekcert, All Rights Reserved.