



4A0-100^{Q&As}

Alcatel-Lucent Scalable IP Networks

Pass Alcatel-Lucent 4A0-100 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/4a0-100.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Alcatel-Lucent Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

In an MPLS network, which device is responsible for taking an unlabeled packet and encapsulating it with an MPLS label?

- A. Ingress Label Edge Router
- B. Egress Label Edge Router
- C. Label Switching Router
- D. Next Hop Router

Correct Answer: A

QUESTION 2

What protocol is used by ping to verify IP network reachability?

- A. DHCP
- B. ICMP
- C. ARP
- D. NAT

Correct Answer: B

QUESTION 3

Which of the following is a characteristic of ATM?

- A. Application data is transported in 53-byte cells.
- B. ATM circuits are identified by a VPI/VCI value.
- C. Provides enhanced QoS support with 5 classes of service.
- D. Ideal for multiple services on the same physical line.
- E. All of the above.
- F. None of the above

Correct Answer: E

QUESTION 4



Which of the following is TRUE about a PE router within a service provider's MPLS network?

- A. It resides on the customer premises.
- B. It is not aware of the VPN services provided by the service provider.
- C. It should connect to at least one other PE router.
- D. It should connect to at least one CE device.

Correct Answer: D

QUESTION 5

What does a device do when it receives an ICMP Echo request message that is destined for itself, it then:

- A. Estimates the round trip-time.
- B. Generates an echo reply message.
- C. Calculates the data loss statistics.
- D. Verifies the data field of the message.

Correct Answer: B

[Latest 4A0-100 Dumps](#)

[4A0-100 PDF Dumps](#)

[4A0-100 Study Guide](#)