



4A0-101^{Q&As}

Alcatel-Lucent Interior Routing Protocols and High Availability

Pass Alcatel-Lucent 4A0-101 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/4a0-101.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Alcatel-Lucent Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

What is the default inbound metric for RIP on the Alcatel-Lucent 7750 SR?

- A. Whatever the advertised metric happens to be.
- B. A value of 1.
- C. This must be administratively set as there is no default value.
- D. A value of 15.

Correct Answer: B

QUESTION 2

Which of the following conditions will prevent an OSPF adjacency from reaching the full state? Choose three answers.

- A. MTU mismatch
- B. Incorrect subnet mask
- C. System interface not included in OSPF
- D. Area ID not the same
- E. Different metric set on each end of the link
- F. Router ID not defined

Correct Answer: ABD

QUESTION 3

What are the ways the RID can be created on an Alcatel-Lucent 7750 SR router? (Choose three)

- A. From the last 32 bits of the chassis MAC address
- B. From the first 32 bits of the chassis MAC address
- C. The loopback IP address
- D. By using the command "config router ospf rid X.X.X.X"
- E. From the system IP address
- F. From the highest interface IP address

Correct Answer: ADE



QUESTION 4

Click on the exhibit.

Use this one for 5.2.a

??? LSA for Area 0.0.0.0

Area Id	: 0.0.0.0	Adv Router Id	: 10.10.10.4
Link State Id	: 0.0.0.0 (0)		
LSA Type	: ???		
Sequence No	: 0x8000002e	Checksum	: 0x9744
Age	: 40	Length	: 56
Options	: --R--EV6		
Flags	:	Link Count	: 2
Link Type (1)	: Transit Network	DR Rtr ID (1)	: 10.10.10.4
I/F Index (1)	: 2	DR I/F Index (1)	: 2
Metric (1)	: 100		
Link Type (2)	: P2P Link	Nbr Rtr ID (2)	: 10.10.10.3
I/F Index (2)	: 3	Nbr I/F Index (2)	: 3
Metric (2)	: 50		

What type of OSPFv3 LSA is shown?

- A. Router LSA
- B. Network LSA
- C. Intra-Area Prefix LSA
- D. Link LSA

Correct Answer: A

QUESTION 5

How can a router ID be created on an Alcatel-Lucent 7750 SR router? Choose three answers

- A. From the least significant 32 bits of the chassis MAC address.
- B. From the most significant 32 bits of the chassis MAC address.
- C. From the loopback IP address.
- D. By using the command "config router router-id X.X.X.X"
- E. From the system IP address.
- F. From the highest interface IP address.

Correct Answer: ADE



VCE & PDF

GeekCert.com

<https://www.geekcert.com/4a0-101.html>

2024 Latest geekcert 4A0-101 PDF and VCE dumps Download

[Latest 4A0-101 Dumps](#)

[4A0-101 PDF Dumps](#)

[4A0-101 Practice Test](#)