



4A0-104^{Q&As}

Alcatel-Lucent Services Architecture

Pass Alcatel-Lucent 4A0-104 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/4a0-104.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Alcatel-Lucent Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

What happens by default on a Nokia 7750 SR when a VPLS accepts a tagged frame at the ingress SAP 1/1/1:100?

- A. The FCS is verified and kept in the customer frame. The VLAN tag is kept and transported over the network.
- B. The FCS is verified and kept in the customer frame. The VLAN tag is removed for transport over the network.
- C. The FCS is verified and removed from the frame. The VLAN tag is kept for transport over the network.
- D. The FCS is verified and removed from the frame. The VLAN tag is removed for transport over the network.

Correct Answer: D

QUESTION 2

The SAP 1/1/1:2.3 receives an Ethernet frame with outer VLAN tag 5 and inner VLAN tag 3. Which of the following is TRUE?

- A. The frame is dropped.
- B. The frame's outer tag is changed to match the SAP, and it is accepted.
- C. The frame's outer tag is dropped, and the frame is accepted.
- D. The frame's tags are removed, and the frame is accepted.

Correct Answer: A

QUESTION 3

Which of the following most accurately describes the default behavior of a VPLS regarding the handling of a tagged frame at the ingress of SAP 1/1/1:100?

- A. The FCS is verified and the customer frame is transported intact over the service provider network.
- B. The FCS is verified and kept in the customer frame. The VLAN tag is removed for transport over the network.
- C. The FCS is verified and removed from the frame. The VLAN tag is kept for transport over the network.
- D. The FCS is verified and removed from the frame. The VLAN tag is removed for transport over the network.

Correct Answer: D

QUESTION 4

How many service labels must be signaled to bring up a fully meshed VPLS service among four PE routers?

- A. 1



- B. 4
- C. 6
- D. 8
- E. 12
- F. 24

Correct Answer: E

QUESTION 5

Which service is needed to bridge an ATM service to an Ethernet service?

- A. A-pipe
- B. F-pipe
- C. C-pipe
- D. E-pipe
- E. Bridge service

Correct Answer: D

[4A0-104 PDF Dumps](#)

[4A0-104 VCE Dumps](#)

[4A0-104 Practice Test](#)