

4A0-105^{Q&As}

Alcatel-Lucent Virtual Private LAN Services

Pass Alcatel-Lucent 4A0-105 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.geekcert.com/4a0-105.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Alcatel-Lucent Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



VCE & PDF GeekCert.com

https://www.geekcert.com/4a0-105.html

2024 Latest geekcert 4A0-105 PDF and VCE dumps Download

QUESTION 1

140.1		" DE 1" OE: MO 1400
Which protocol is used to signa	al the status of the active links betw	een the PE and the CE in MC- LAG?

- A. MSTP
- B. MCLAG
- C. LACP
- D. DHCP
- E. A proprietary protocol

Correct Answer: C

QUESTION 2

If the command "disable-learning" has been added at the VPLS level, then MAC entries which have already been learned will not be aged.

- A. TRUE
- B. FALSE

Correct Answer: B

QUESTION 3

When ports configured with IEEE 802.3ah EFM are operationally down, what must the device do before declaring the ports are up?

- A. The device will try to force the other side up using the evaluating flag in the PDU.
- B. The device will wait for the trasmit-interval of 5 before trying to rediscover the neighbor.
- C. The device will detect the port change and will wait for normal operation mode.
- D. The device will detect the port change and revert to discovery mode.

Correct Answer: D

QUESTION 4

Which element of IEEE 802.1ag is responsible for initiating CFM messages?

- A. MEP
- B. MAP



https://www.geekcert.com/4a0-105.html

2024 Latest geekcert 4A0-105 PDF and VCE dumps Download

C. MIP

D. MUP

Correct Answer: A

QUESTION 5

Click on the exhibit below.

```
PE1>service# vpls 1 customer 1 m-vpls create
PE1>service>vpls# mesh-sdp 500:1 create
PE1>service>vpls>mesh-sdp# exit
PE1>service>vpls# no shutdown
PE1>service>vpls# spoke-sdp 900:1 create
PE1>service>vpls# spoke-sdp# exit
PE1>service>vpls* exit

PE1>service>vpls# exit

PE1>service# vpls 100 customer 1 create
PE1>service>vpls# mesh-sdp 500:100 create
PE1>service>vpls# mesh-sdp# exit
PE1>service>vpls# no shutdown
PE1>service>vpls# mesh-sdp 900:100 create
PE1>service>vpls# mesh-sdp 900:100 create
PE1>service>vpls# mesh-sdp 900:100 create
```

Given the following configuration, which service type will VPLS 1 and VPLS 100 be displayed as with the "show service service-using" command?

- A. VPLS 1 will be displayed as mVPLS and VPLS 100 will be displayed as VPLS.
- B. VPLS 1 will be displayed as mVPLS and VPLS 100 will be displayed as uVPLS
- C. VPLS 1 will be displayed as VPLS and VPLS 100 will be displayed as VPLS.
- D. VPLS 1 will displayed VPLS and VPLS 100 will be displayed as uVPLS.

Correct Answer: A

Latest 4A0-105 Dumps

4A0-105 PDF Dumps

4A0-105 VCE Dumps