



# 4A0-M10<sup>Q&As</sup>

Nokia 5G Packet Core Architecture

**Pass Nokia 4A0-M10 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/4a0-m10.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Which of the following statements about Option 3X dual connectivity is FALSE?

- A. VoLTE traffic is handled by the LTE network.
- B. Dual connectivity is used for high throughput services such as eMBB.
- C. When NR radio quality becomes sub-optimal, gNB decides to split the bearer.
- D. Both eNB and gNB are connected with S1-U interfaces to SGW.

Correct Answer: A

---

### QUESTION 2

Which of the following actions is performed when an idle UE moves from 5GS to EPS and the N26 interface is used?

- A. UE initiates an Attach procedure and includes an EPS-GUTI derived from its 5G-GUTI.
- B. For any PDU session that supports interworking, the serving SMF provides an SM context that includes mapped EPS bearers to the AMF.
- C. AMF selects an SGW to serve the UE, and then sets up the required S5-U and S5-C GTP tunnels on the selected SGW.
- D. AMF uses the EPS-GUTI derived from the UE 5G-GUTI to discover the MME, and then provides the UE context to the MME.

Correct Answer: C

---

### QUESTION 3

Which of the following statements about non-access stratum mobility management (NAS-MM) protocol is TRUE?

- A. It runs between the UE and the SMF.
- B. It is used to control user plane resources between the UE and a data network.
- C. It provides common procedures such as authentication, identification, and UE configuration update.
- D. NAS-MM messages are relayed transparently by the AMF.

Correct Answer: C

---



#### QUESTION 4

Which of the following elements is NOT used in the 5G non-standalone (NSA) deployment Option 3?

- A. Evolved Packet Core
- B. ng-eNB
- C. gNB
- D. Dual Radio UE

Correct Answer: A

Reference: <https://www.gsma.com/futurenetworks/wiki/5g-implementation-guidelines/>

---

#### QUESTION 5

Which of the following statements about QoS profiles used in 5G is FALSE?

- A. SMF derives the QoS profile of a QoS Flow from a PCC rule and sends it to NG-RAN.
- B. NG-RAN uses the QoS profiles to create mapping between QoS Flow IDs and data radio bearers.
- C. NG-RAN sends the QoS profiles and corresponding QoS Flow IDs to the UE.
- D. Each QoS profile includes a 5G QoS Identifier (5QI) and an Allocation and Retention Priority (ARP).

Correct Answer: C

[4A0-M10 PDF Dumps](#)

[4A0-M10 Practice Test](#)

[4A0-M10 Study Guide](#)