



4A0-M10^{Q&As}

Nokia 5G Packet Core Architecture

Pass Nokia 4A0-M10 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/4a0-m10.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which of the following statements about Option 3X dual connectivity is FALSE?

- A. VoLTE traffic is handled by the LTE network.
- B. Dual connectivity is used for high throughput services such as eMBB.
- C. When NR radio quality becomes sub-optimal, gNB decides to split the bearer.
- D. Both eNB and gNB are connected with S1-U interfaces to SGW.

Correct Answer: A

QUESTION 2

Which of the following is an HTTP method used by an NF service consumer to create a new resource at an NF service producer when the resource URI is selected by the consumer?

- A. POST
- B. PUT
- C. PATCH
- D. UPDATE

Correct Answer: B

Reference: https://www.tech-invite.com/3m29/toc/tinv-3gpp-29-501_c.html

QUESTION 3

A UE is handed off from gNB1 to gNB2 using an N2-based handover procedure. The source I-UPF is to be relocated and an indirect data forwarding path is to be used. Which of the following statements is TRUE?

- A. AMF decides that an indirect data forwarding path is required and sends an indication to SMF.
- B. gNB2 tunnel info is allocated for the indirect forwarding path and is included in the Handover Request Ack message sent to AMF.
- C. Target I-UPF tunnel info is allocated for the indirect forwarding path and is provided to the UPF PSA.
- D. UPF PSA tunnel info is allocated for the indirect forwarding path and is provided to the source I-UPF.

Correct Answer: A



QUESTION 4

Which of the following statements about non-access stratum mobility management (NAS-MM) protocol is TRUE?

- A. It runs between the UE and the SMF.
- B. It is used to control user plane resources between the UE and a data network.
- C. It provides common procedures such as authentication, identification, and UE configuration update.
- D. NAS-MM messages are relayed transparently by the AMF.

Correct Answer: C

QUESTION 5

Which of the following elements is NOT used in the 5G non-standalone (NSA) deployment Option 3?

- A. Evolved Packet Core
- B. ng-eNB
- C. gNB
- D. Dual Radio UE

Correct Answer: A

Reference: <https://www.gsma.com/futurenetworks/wiki/5g-implementation-guidelines/>

[4A0-M10 PDF Dumps](#)

[4A0-M10 Exam Questions](#)

[4A0-M10 Brindumps](#)