



500-440^{Q&As}

Designing Cisco Unified Contact Center Enterprise (UCCED)

Pass Cisco 500-440 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/500-440.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which type of traffic from the peripheral gateway to the central controller is considered high priority in the Cisco Unified Contact Center Enterprise solution?

- A. configuration requests
- B. skill group data
- C. routing and DMP control traffic
- D. Real-Time Monitoring

Correct Answer: C

QUESTION 2

A Cisco Unified Contact Center Enterprise solution is designed with geographic redundancy for the central controllers (with separate call routers and loggers). If Call Router Side A has device majority and its Ethernet private network NIC fails, which two events occur? (Choose two.)

- A. Both sides go out of service for small period of time, Call Router Side A goes active, and Call Router Side B goes idle
- B. Both sides go in service for small period of time, Call Router Side A goes active after negotiations with Call Router Side B, Call Router Side B goes idle
- C. There is no ability to make ICM configuration changes at Side B
- D. The Call Router Side A stays active, while Call Router Side B goes idle
- E. The Call Router Side B stays active, while the Call Router Side A goes idle

Correct Answer: CD

QUESTION 3

Which setup is correct when you configure the Cisco UCS B VICs to reach the Fabric Interconnect Switches for the Cisco UCCE on UCS B deployments?

- A. Disable the Fabric Failover only when the UCS B FI connects to a Disjointed L2 domain in the upstream network
- B. Enable the Fabric Failover to reach both Fabric Interconnect A and B in HA paths
- C. Disable the Fabric Failover option.
- D. Enable the Fabric Failover only when the UCS B FI connects to a Common L2 domain in the upstream network

Correct Answer: C



QUESTION 4

Which two features does Cisco Unified Border Element provide when Cisco Unified CCE and Cisco Unified Customer Voice Portal are used? (Choose two.)

- A. load balancing outbound calls
- B. secure communication using flow around mode
- C. normalize SIP messages using SIP profiles
- D. Silent Monitor inbound voice calls
- E. record calls by forking the media

Correct Answer: AC

QUESTION 5

Which statement about the Cisco UCCE solution in the virtualized environment is true?

- A. VMware NIC teaming whether in active-active or active-standby configuration on the UCS B/C series is supported
- B. Nexus 1000V virtual distributed switch can be used but only for 500 agent deployment model
- C. Cisco UCS VIC can be used on UCS C series TRC models
- D. Spec-based virtualized servers based on Intel E5 26xx cpu family at speed 2.40 GHz is supported

Correct Answer: D

[500-440 VCE Dumps](#)

[500-440 Study Guide](#)

[500-440 Exam Questions](#)