



# 500-601<sup>Q&As</sup>

Application Centric Infrastructure Support Representative

## Pass Cisco 500-601 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/500-601.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

Where does the subnet address of the distributed gateway need to be configured when route leaking is required?

- A. under the contract provider EPG
- B. under the contract consumer EPG
- C. in a shared bridge domain in the tenant common
- D. in the endpoint bridge domain

Correct Answer: D

---

### QUESTION 2

What is the minimal number of operational Cisco APICs in a cluster that are needed to ensure that policy modification is still possible?

- A. 3
- B. 2
- C. 4
- D. 1

Correct Answer: A

---

### QUESTION 3

A VMM endpoint off of a UCSB is unable to hit its anycast gateway, but the MAC address of the VM can be seen in one of the fabric interconnects. Which option is the cause of the issue?

- A. The active NIC on the host has gone down and the host has not yet failed over.
- B. There is no native VLAN configured within the data path of the Cisco UCS.
- C. LLDP is not enabled in the vSwitch policies.
- D. The VLAN tag is being changed at the vNIC or uplink port.

Correct Answer: D

---

### QUESTION 4

Which three AVS switching modes are supported on Cisco ACI? (Choose three)

- A. VXLAN, no local switching



- B. VPC-HM
- C. VXLAN, local switch
- D. VLAN, no local switching
- E. MAC pinning
- F. VLAN, local switching

Correct Answer: ADF

---

#### QUESTION 5

Which two statements about troubleshooting common ARP forwarding issues ma Cisco ACI Fabric are true? (Choose two.)

- A. If IPManager On the spine rejected a tenant VRF/route configuration, the spine command show ip route vrf can be used to verify all tenant VRF configurations.
- B. The BD SVI IP address can be verified with the vsh\_ lc show platform internal ns forwarding router-ip command.
- C. The tcpdump command can be used on all Cisco ACI switches to capture and verity tenant EPGdata plan traffic.
- D. The VLAN membership for an interface on the Broadcom ASIC can be verified with the show hardware vlans programmed command.
- E. VLAN membership of an Interface can be vended wrth the VSh\_IC show system Internal eltmc Info interface x/x command.

Correct Answer: CD

[Latest 500-601 Dumps](#)

[500-601 Practice Test](#)

[500-601 Study Guide](#)