



# 500-601<sup>Q&As</sup>

Application Centric Infrastructure Support Representative

## Pass Cisco 500-601 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/500-601.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





#### QUESTION 1

Which two actions occur when an EPG is being validated on a switch? (Choose two.)

- A. IDs assignment validation
- B. VLAN validation
- C. path validation
- D. BD, CTX configured validation

Correct Answer: BC

---

#### QUESTION 2

Which command is used to successfully SSH into a Cisco ARC or switch CLI using a remote authentication server?

- A. apic#rad\_check//username@192.168.1.21
- B. ssh apic#rad\_check\\username@192.168.1.21
- C. ssh apic#ad\_ch?k//username@192.168.1.21
- D. ssh apic@rad\_check\\username@192.168.1.21

Correct Answer: C

---

#### QUESTION 3

Which three AVS switching modes are supported on Cisco ACI? (Choose three)

- A. VXLAN, no local switching
- B. VPC-HM
- C. VXLAN, local switch
- D. VLAN, no local switching
- E. MAC pinning
- F. VLAN, local switching

Correct Answer: ADF

---

#### QUESTION 4

Which two statements about the Cisco ACI distributed gateway are true? (Choose two.)



- A. Endpoints attached to a leaf always find their gateway locally on the attached leaf.
- B. The routing function of the SVI is performed on the leaf in the Northstar ASIC.
- C. Endpoint mobility is restricted to a specific port on a specific leaf.
- D. The routing function of the SVI is performed on the leaf in the Trident 2 Broadcom ASIC.
- E. Gateway is represented as a SVI.

Correct Answer: BD

---

#### QUESTION 5

Which three statements about logical, resolved, and concrete model in Cisco ACI are true? (Choose three.)

- A. Objects in the resolved model are read-only objects that are used to pass the configuration object from the Cisco APIC to the needed switches.
- B. Objects in the concrete model are concrete real objects that are configured by a user.
- C. Objects in the logical model are read/write objects that are configured by a user.
- D. iNXOS consumes objects from the concrete model to program switch hardware with the needed networking construct, such as vlan or vrf.
- E. iNXOS consumes objects from the resolved model to program switch hardware with the needed networking construct, such as vlan or vrf.
- F. NXOS consumes objects from the logical model to program switch hardware with the needed networking construct, such as vlan or vrf.

Correct Answer: BCD

[500-601 VCE Dumps](#)

[500-601 Study Guide](#)

[500-601 Braindumps](#)