



# 500-601<sup>Q&As</sup>

Application Centric Infrastructure Support Representative

## Pass Cisco 500-601 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/500-601.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Which command allows you to log in to a line card on a leaf switch?

- A. Leaf# vsh\_lc
- B. Leaf#vsh
- C. Leaf\*vsh-lc
- D. Leaf# vshell -lc
- E. Leaf# vsh-hw

Correct Answer: E

### QUESTION 2

Refer to the exhibit The configured bridge domain with name "Prod-BD" m tenant Prod is not functioning property Which option describes a possible reason for that failure?

```
# fv . RsCtx
childAction      :
Dn               : uni/tn-Prod/BD-Prod-BD/rsctx
forceResolve     : yes
lcOwn            : local
modTs            : 2015-06-12T15:03:08.016+01:00
monPolDn         : uni/tn-common/monepg-default
rType            : mo
Rn               : rsctx
State            : missing-target
stateQual        : none
Status           :
tCl              : fvCtx
tContextDn       :
tDn              :
tRn              : ctx-Prod-vrf
tType            : name
tnFvCtxName      : prod-vrf
uid              : 0
```



- A. The context "Prod-vrf" does not exist in the fabric.
- B. The "missing-target" state field indicates that there are not leaves with endpoint in the bridge domain, so it is not configured anywhere.
- C. Someone has deleted the monitoring object "monepg default".
- D. The tenant "Prod" has been deleted.

Correct Answer: A

---

### QUESTION 3

Which two statements are true regarding ARP request/response on an ACI Fabric? (Choose two.)

- A. ARP requests come in on the elected/designated FD encapsulation VLAN under the BD.
- B. ARP request can be captured using icpdump" on spine switches.
- C. ARP traffic is handled by the broadcom ASIC if the two endpoints are in the same EPG and the same FD VLAN.
- D. ARP requests are sent to CPU only if they are for the Bridge Domain SVI IP address
- E. ELAM can be used to capture ARP request/response frames in the Leaf front panel Broadcom ASIC.

Correct Answer: DE

---

### QUESTION 4

In the Cisco APIC, how are fabric-wide unique identifiers managed?

- A. dme
- B. coop
- C. eltmc
- D. idmgr

Correct Answer: A

---

### QUESTION 5

Refer to the exhibit Which IP address is displayed?



```
admin@pic1:~> acidiag fmvread
```

ID	Name	Serial Number	IP Address	Role	State	LastUpdMsgId
101	Leaf101		10.0.224.95/32	Leaf	active	0
102	Leaf102		10.0.224.92/32	Leaf	active	0
103	Leaf103		10.0.224.91/32	Leaf	active	0
104	Leaf104		10.0.224.90/32	Leaf	active	0
201	Spine201		10.0.224.94/32	Spine	active	0
202	Spine202		10.0.224.93/32	Spine	active	0

Total 6 nodes

- A. infrastructure IP
- B. out-of-band IP
- C. management IP
- D. in-band IP

Correct Answer: D

[Latest 500-601 Dumps](#)

[500-601 Practice Test](#)

[500-601 Study Guide](#)