



500-901^{Q&As}

Cisco Data Center Unified Computing Infrastructure Design

Pass Cisco 500-901 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/500-901.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

How do service profiles enable workload mobility?

- A. Service Profiles represent a physical view of a server without any ties to specific virtual hardware
- B. Service Profiles work with the underlying hypervisor and communicate with the VM to detect workload movement
- C. Service Profiles represent a logical view of a server without any ties to specific physical hardware
- D. Service Profiles communicate workload movement to VCenter

Correct Answer: A

QUESTION 2

An administrator has configured an NPV traffic map for a new server interface, none of the uplinks in the traffic map are open action?

- A. The traffic map will be disregarded and an uplink in the interface VSAN will be selected.
- B. The default VSAN uplink will be used if operational.
- C. The server will remain in a nonoperational state.
- D. The server interface will signal an FDISC message to the fabric switch.

Correct Answer: C

QUESTION 3

How many QoS classes are available to administrators on Cisco's UCS server?

- A. 6
- B. 4
- C. 2
- D. 8

Correct Answer: A

QUESTION 4

Cisco recommended to help customer's provision physical, virtual, and multivendor data center infrastructure environments from a single pane?

- A. Cisco UCS Director



B. Cisco UCS Performance Manager

C. Cisco UCS Manager

D. Cisco UCS Central

Correct Answer: C

QUESTION 5

An administrator is setting up a new VSAN and needs to use IVR to allow access to backup tape storage targets located in a different VSAN. There is an existing Nexus 5K switch in the SAN fabric that the admin would like to use; however, the switch is not IVR-enabled.

How can the Cisco Nexus switch be used?

A. It cannot be used, since only MDS Switches implement IVR.

B. As a Transit switch.

C. As a Border switch or IVR NAT gateway.

D. As an Edge switch.

Correct Answer: D

[500-901 PDF Dumps](#)

[500-901 Practice Test](#)

[500-901 Exam Questions](#)